Approved as Noted

GOVERNING STANDARD PLANS:

http://www.fdot.gov/design/Standardplans.shtm

GOVERNING STANDARD SPECIFICATIONS:

at the following website:

APPLICABLE IRs: N/A

Florida Department of Transportation, FY2025-26 Standard plans for

Road and Bridge Construction and applicable Interim Revisions (Irs).

Standard Plans for Road Construction and associated Irs are available

Standard Plans for Bridge Construction are included in the Structures

Florida Department of Transportation, FY 2025-26 Standard

Specifications for Road and Bridge Construction at the following

http://www.fdot.gov/programmanagement/Implemented/SpecBooks

Public Works Plans Examiner


PLANS

SHEET NO.	SHEET DESCRIPTION
L-1	KEYSHEET
L-2 - L-5	TABULATION OF QUANTITIES
L-6 - L-7	GENERAL NOTES
L-8	TYPICAL SECTIONS
L-9	LEGEND
L-10 - L-13	POLE DATA
L-14	PROJECT LAYOUT
L-15 - L-36	LIGHTING PLANS
L-37 - L-38	SERVICE POINT ELECTRICAL DETAILS
L-39	LIGHT POLE DETAIL

CITY OF DORAL, FLORIDA

TRAIL LIGHTING IMPROVEMENT PLANS

TURNPIKE TRAIL ALONG NW 117TH AVE FROM NW 25TH ST TO NW 58TH ST



DERM - Water Control Section

Class III permit 20240082 is in effect for the installation of lighting

along the pedestrian trails within existing Canal Maintenance

Easement along No	rthline, Dressels Dairy and	l Snapper Creek
and Snapper Cree	k Extension Canals.	
CHECK Rogelio Mata	RECOMMENDED (Allmare)	APPROVED
Date _05/01/2025	File No. 20240082	Sheet of

1.The project must adhere to City of Doral Code of Ordinances, Chapter 38-22, and all other relevant municipal, state, and federal laws

2.Regulatory Compliance Assurance:

The registrant agrees at all times to comply with and abide by all applicable provisions of state statutes, city ordinances, codes, and regulations when placing or maintaining a communications facility in public rights-of-way

-A registrant shall not commence placing or maintaining a communications facility in public rights-of-way until all applicable permits have been issued by the city or other

-Contractors must coordinate with the Transportation Department and provide advance notice of the start date, considering that several routes may be impacted by the

4.Installation Methodology

A detailed description of the facility installation method (e.g., anticipated construction methods and techniques) must be provided.

5.Construction Timetable:

A construction schedule outlining each project phase and the areas of the city affected must be submitted.

6.Right-of-Way Use and Protection:

oAll communications facilities shall be placed and maintained to avoid unreasonable interference with public use of rights-of-way and to minimize inconvenience to

-The registrant shall install facilities underground wherever possible Trenchless technology (e.g., directional bore method), joint trenching, or co-location in existing conduits may be required based on feasibility and impact assessments.

-The registrant is responsible for any displacement, damage, or destruction of landscaping, irrigation systems, or other property within the public rights-of-way. -Equipment or material storage must be outside of the pavement or on the swale areas, ensuring it does not hinder bus operations.

7.Restoration Requirements:

The registrant must restore public rights-of-way to their original or better condition at their own expense, subject to city inspection and approval.

- No sand blasting, water blasting, asphalt patching will be allowed. full lane and/or intersection restoration will be required
-Restoration must meet Miami-Dade County Public Works (MDCPW) standards, and the final restoration must align with what the City of Doral considers appropriate.

-A 12-month warranty period applies to restored areas. -Failure to complete restoration within 30 calendar days may result in the city completing the work and recovering costs from the registrant as per F.S. § 337.402.

-Property owners adjacent to the work area must be notified at least 24 hours prior to the commencement of work

9.Property Access Maintenan

-Uninterrupted access to adjacent properties must be maintained at all times during construction.

-Upon project completion, the site must be restored to its original or improved condition at the sole cost of the permit applicant.

-No lane closures or traffic interruptions are permitted during AM and PM peak hours (7:00 AM - 9:00 AM & 4:00 PM - 6:00 PM). -A Maintenance of Traffic (MOT) Plan must be submitted and approved by the City of Doral and MDCPW.

-The MOT must include the use of cones, barricades, caution tape, lighting, signs, and the proper use of flaggers and/or law enforcement officers

12.Agency Approvals:

Miami-Dade County Public Works (MDCPW) approval is required for work impacting county roadways.

-Fire Department approval may also be required for access considerations 13.Traffic Study and Compliance

-A Trip Generation and/or Traffic Study may be required to assess the impact of the proposed facility. Contact the City Traffic Engineer for guidance.

Coordination with local utility providers (e.g., MDWASD, FPL) is required to prevent conflicts and ensure proper relocation if needed

15.Erosion and Sediment Control:

-Erosion control measures must be implemented per Florida Greenbook standards to prevent runoff and environmental impact.

Periodic inspections will be conducted by city officials to ensure compliance with permit conditions and quality standards

17. Public Safety Considerations:

-Contractors must set up and implement a program to protect persons and property in the event of emergencies and take immediate action to correct unsafe practices and

unsafe conditions. Ensure pedestrian access and ADA compliance for temporary and permanent facilities, including sidewalk detours and safety measures.

-All personnel working on the project shall wear, at a minimum, hard hats and Type II reflective clothing.
-Pedestrian/patron access to bus stops in the project limits shall not be interrupted. Transit prefers no full closure unless discussed with Transit

.Equipment or material storage must be outside of the pavement

-A drainage plan must be submitted detailing how stormwater will be managed to comply with approved paving and drainage plans.

19. Signage and Pavement Markings: All traffic control devices must comply with the Manual on Uniform Traffic Control Devices (MUTCD) standards

20.Construction Noise and Hours: -Work hours must comply with city noise ordinances to minimize disturbances to nearby properties.

21.Tree Protection and Landscaping:

Compliance with city landscaping codes is required, and existing trees within the right-of-way must be protected during construction

ERON

THIS ITEM HAS BEEN DIGITALLY SIGNED AND SEALED BY

Joseph M Calderon Torres 2025.04.08 14:53:13-04'00'

ON THE DATE ADJACENT TO THE SEAL

PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES

LIGHTING PLANS ENGINEER OF RECORD:

JOSEPH M. CALDERON TORRES II, P.E. P.E. NO.: 90625 H.W. LOCHNER, INC 8750 N.W. 36TH STREET, SUITE 360 MIAMI, FLORIDA 33178 TEL: (305) 503-9873; FAX: (305) 503-9882 VENDOR NO .: VF-362-338-11

PERMIT SUBMITTAL

SHEET NO.

L-1

PSJ\000021994\700_CADD\Lighting\Turnpike Trail\KEYSLT01.dwg

CITY OF DORAL **Public Works Department**

Permit #PWUT-2505-0061 RECEIVED: 05/06/2025

CITY OF DORAL

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025

TABULATION OF QUANTITIES

5.4)								S	HEET NUMBER	R <i>S</i>						TAL	GR	AND
PAY ITEM	DESCRIPTION	UNIT	L-	- 15	L-	- 16	L-	- 17	L - 18	L-	- 19	L-	20	L-21		HIS EET		TAL
NO.			PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN FINAL	PLAN	FINAL	PLAN	FINAL	PLAN FINAL	PLAN	FINAL	PLAN	FINAL
630-2-11	CONDUIT, FURNISH & INSTALL, OPEN TRENCH	LF	370		529		87		455	567		544		561	3113			
630-2-12	CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE	LF	77		39				76						192			
635 - 2 - 11	PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE	EA	8		2		2		8	9		8		8	45			
639-1-112	ELECTRICAL POWER SERVICE, F&I, OVERHEAD, METER PURCHASED BY CONTRACTOR	AS					1								1			
639 - 1 - 122	ELECTRICAL POWER SERVICE, F&I, UNDERGROUND, METER PURCHASED BY CONTRACTOR	AS																
639 - 2 - 1	ELECTRICAL SERVICE WIRE, FURNISH & INSTALL	LF																
641-2-12	PRESTRESSED CONCRETE POLE, F&I, TYPE P-II SERVICE POLE	EA																
641 - 2 - 15	PRESTRESSED CONCRETE POLE, F&I, TYPE P-V	EA					1								1			
715-1-12	LIGHTING CONDUCTORS, F&I, INSULATED, NO.8 - 6	LF																
715-1-13	LIGHTING CONDUCTORS, F&I, INSULATED, NO.4 - 2	LF	2091		1824		261		2217	2349		2403		2325	13470			
715-7-11	LOAD CENTER, F&I, SECONDARY VOLTAGE	EA					1								1			
715-516-11	0 LIGHT POLE COMPLETE, DIRECT BURIED, F&I, POLE TOP MOUNT, 10'	EA	8						8	9		8		8	41			
				1			1	1		1		L				1		

	REVISIONS	
DATE	DESCRIPTION	
		Lochner
		LOCI II ICI

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



TABULATION OF QUANTITIES	ı	
--------------------------	---	--

SHEET NO.

TABULATION OF QUANTITIES

CITY OF DORAL
Public Works Department Permit #PWUT-2505-0061
RECEIVED: 05/06/2025

D 4)/								S	HEET I	NUMBER	25							TAL	GR	AND
PAY ITEM	DESCRIPTION	UNIT	L - 22		L - 23		L-	-24	L -	25	L -	26	L -	27	L-	28		HIS EET		TAL
NO.			PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL
630-2-11	CONDUIT, FURNISH & INSTALL, OPEN TRENCH	LF	570		485		566		566		566		<i>352</i>		566		3671			
630-2-12	CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE	LF											295				295			
635-2-11	PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE	EA	9		10		9		10		10		7		9		64			
639 - 1 - 112	ELECTRICAL POWER SERVICE, F&I, OVERHEAD, METER PURCHASED BY CONTRACTOR	AS																		
639 - 1 - 122	ELECTRICAL POWER SERVICE, F&I, UNDERGROUND, METER PURCHASED BY CONTRACTOR	AS											1				1			
639-2-1	ELECTRICAL SERVICE WIRE, FURNISH & INSTALL	LF											94				94			
641-2-12	PRESTRESSED CONCRETE POLE, F&I, TYPE P-II SERVICE POLE	EA											1				1			
641-2-15	PRESTRESSED CONCRETE POLE, F&I, TYPE P-V	EA																		
715-1-12	LIGHTING CONDUCTORS, F&I, INSULATED, NO.8 - 6	LF			1971		2448		2439		2070		345		2346		11619			
715-1-13	LIGHTING CONDUCTORS, F&I, INSULATED, NO.4 - 2	LF	2280		132						348		1602				4362			
715-7-11	LOAD CENTER, F&I, SECONDARY VOLTAGE	EA											1				1			
715-516-110	LIGHT POLE COMPLETE, DIRECT BURIED, F&I, POLE TOP MOUNT, 10'	EA	9		10		8		10		10		3		9		59			

	REVISIONS	
DATE	DESCRIPTION	



JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*

ST OF DOR
PORIDA

TABULATION OF QUANTITIES	
--------------------------	--

SHEET NO. L-3

TABULATION OF QUANTITIES

CITY OF DORAL
Public Works Department Permit #PWUT-2505-0061
RECEIVED: 05/06/2025

D 41/			SHEET NUMBERS															TAL	GRAND	
PAY ITEM	DESCRIPTION	UNIT	L-	L - 29		L - 30		- 31	L -	<i>32</i>	L-	33	L - 34		L - 35		THIS SHEET		TOTAL	
NO .			PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	F I N
630 - 2 - 11	CONDUIT, FURNISH & INSTALL, OPEN TRENCH	LF	566		569		306		512		582		513		566		3614			
630-2-12	CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE	LF																		
535-2-11	PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE	EA	8		10		6		9		12		9		10		64			
639 - 1 - 112	ELECTRICAL POWER SERVICE, F&I, OVERHEAD, METER PURCHASED BY CONTRACTOR	AS									1						1			
539 - 1 - 122	ELECTRICAL POWER SERVICE, F&I, UNDERGROUND, METER PURCHASED BY CONTRACTOR	AS																		
539-2-1	ELECTRICAL SERVICE WIRE, FURNISH & INSTALL	LF																		
541-2-12	PRESTRESSED CONCRETE POLE, F&I, TYPE P-II SERVICE POLE	EA																		
541-2-15	PRESTRESSED CONCRETE POLE, F&I, TYPE P-V	EA									1						1			
15-1-12	LIGHTING CONDUCTORS, F&I, INSULATED, NO.8 - 6	LF	2322		2379		1326		2202		1767		1490		1716		13202			
715-1-13	LIGHTING CONDUCTORS, F&I, INSULATED, NO.4 - 2	LF									1160		713		822		2695			
715-7-11	LOAD CENTER, F&I, SECONDARY VOLTAGE	EA									1						1			
715-516-110	LIGHT POLE COMPLETE, DIRECT BURIED, F&I, POLE TOP MOUNT, 10'	EA	8		10		6		9		9		10		10		62			
																				+

REVISIONS	
DESCRIPTION	DATE

ochner

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*

SY OF DOR
LORIDA

TABULATION OF QUANTITIES	
	1

SHEET NO. L-4

TABULATION OF QUANTITIES

CITY OF DORAL
Public Works Department Permit #PWUT-2505-0061
RECEIVED: 05/06/2025

D 41/			SHEET NUMBERS												TAL	GR	AND			
PAY ITEM	DESCRIPTION	UNIT	L	L - 36									THIS SHEET			TOTAL				
NO .			PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL
630-2-11	CONDUIT, FURNISH & INSTALL, OPEN TRENCH	LF	248														248		10646	1
630-2-12	CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE	LF																	487	
635-2-11	PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE	EA	6														6		179	
639-1-112	ELECTRICAL POWER SERVICE, F&I, OVERHEAD, METER PURCHASED BY CONTRACTOR	AS																	2	
639 - 1 - 122	ELECTRICAL POWER SERVICE, F&I, UNDERGROUND, METER PURCHASED BY CONTRACTOR	AS																	1	
639-2-1	ELECTRICAL SERVICE WIRE, FURNISH & INSTALL	LF																	94	
641-2-12	PRESTRESSED CONCRETE POLE, F&I, TYPE P-II SERVICE POLE	EA																	1	
641-2-15	PRESTRESSED CONCRETE POLE, F&I, TYPE P-V	EA																	2	
715-1-12	LIGHTING CONDUCTORS, F&I, INSULATED, NO.8 - 6	LF	932														932		25753	
715-1-13	LIGHTING CONDUCTORS, F&I, INSULATED, NO.4 - 2	LF	474														474		21001	
715-7-11	LOAD CENTER, F&I, SECONDARY VOLTAGE	EA																	3	
715-516-110	LIGHT POLE COMPLETE, DIRECT BURIED, F&I, POLE TOP MOUNT, 10'	EA	6														6		168	
																				+

	REVISIONS	
DATE	DESCRIPTION	



JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



TABULATION OF QUANTITIES	
--------------------------	--

SHEET NO. L-5

GENERAL NOTES

- CONTRACTOR TO FURNISH AND INSTALL THE ELECTRICAL SYSTEM AS DEPICTED ON ELECTRICAL DRAWINGS.
- THE ELECTRICAL CONTRACTOR TO PROVIDE ALL MATERIALS AND LABOR TO INSTALL THE ELECTRICAL SYSTEMS AS INDICATED ON THE DRAWINGS. IT IS NOT THE INTENT OF THESE PLANS TO SHOW EVERY MINOR DETAIL OF CONSTRUCTION. ITEMS NOT SHOWN BUT OBVIOUSLY NECESSARY FOR COMPLETION OF THE WORK SHALL BE INCLUDED.
- 3. THE INSTALLATION SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, NFPA-70, 2020, FLORIDA BUILDING CODE, EIGHTH EDITION 2023, NFPA-101 2021, LOCAL CODES, AND OTHER APPLICABLE JURISDICTION CODES.
- THE CONTRACTOR TO OBTAIN ALL NECESSARY PERMITS, INSPECTIONS, AND APPROVALS. ALL WORK SHALL BE DONE BY A LICENSED ELECTRICIAN.
- THE CONTRACTOR TO COORDINATE THE WORK WITH THE ENGINEER AND OWNER.
- 6 THE CONTRACTOR SHALL DETERMINE THE SERVICE REQUIRED DATE FOR THE POWER COMPANY CONFERENCE
- GROUNDING TO BE INSTALLED TO MEET NEC. ARTICLE 250 REQUIREMENTS. A GROUNDING SYSTEM SHALL NOT EXCEED A 48-HOUR DRY RESISTANCE OF 10 OHMS. ADDITIONAL GROUNDING TO MEET THIS REQUIREMENT SHALL BE INSTALLED AT NO EXTRA COST. GROUNDING AND BONDING CONNECTIONS SHALL NOT BE PAINTED. TESTING SHALL BE PERFORMED IN THE PRESENCE OF THE ENGINEER. AN EQUIPMENT GROUND WIRE SIZED PER NEC SHALL BE PULLED IN ALL ELECTRICAL CONDUITS.
- ALL EQUIPMENT AND MATERIALS SHALL BE NEW, FURNISHED, AND UL LISTED
- 9. UNDERGROUND CONDUITS SHALL BE SCHEDULE 40 PVC. ALL ABOVE GRADE CONDUITS SHALL BE RIGID GALVANIZED STEEL CONDUIT.
- 10. ELECTRICAL WARNING TAPE SHALL BE PLACED 12 INCHES DEEP ON TOP OF ALL UNDERGROUND TRENCHES
- 11. ALL TRENCHES SHALL BE FILLED WITH COMPACTED EXISTING CLEAN BACKFILL (98% AASHTO T-99) AND COMPACTED UTILIZING COMPACTION MACHINE AT DEPTH OF NOT MORE THAN 6 INCH LAYERS.
- 12. ALL UNDERGROUND ELECTRICAL CONDUITS SHALL BE A MINIMUM OF 24 INCHES DEEP TO TOP OF BRANCH CIRCUIT CONDUIT AND 36 INCHES DEEP TO THE TOP OF FEEDER CONDUIT FROM FPL TRANSFORMER, UNLESS NOTED OTHERWISE.
- 13. INSTALL PULL BOXES AS NECESSARY TO ACCOMMODATE LONG CABLE PULLS. INSTALL DUCT SEALS AT END OF CONDUITS THAT ENTER PULL BOXES, AND JUNCTION BOXES. LEAVE A MINIMUM OF 6 INCH SPACE BETWEEN WIRES AND PULL BOX COVERS.
- 14. THE DRAWINGS ARE NOT INTENDED TO SHOW THE EXACT LOCATION OF CONDUIT RUNS. TRENCHING SHALL BE COORDINATED WITH OTHER TRADES SUCH AS LANDSCAPING, AND OTHER UNDERGROUND UTILITIES SO THAT CONFLICTS ARE AVOIDED PRIOR TO INSTALLATION. ADDITIONALLY, MAINTAIN ENOUGH DISTANCE FROM EXISTING TREES AND LANDSCAPE AREAS SUCH THAT MINIMUM DAMAGE IS DONE TO EXISTING ROOTS.
- 15. THE CONTRACTOR IS RESPONSIBLE TO TEST ALL SYSTEMS AND REPAIR OR REPLACE ALL DEFECTIVE WORK TO THE SATISFACTION OF THE ENGINEER AND OWNER
- 16. TYPE WRITTEN PANEL SCHEDULE SHALL BE INSTALLED IN THE PANEL BOARDS. ALL CIRCUITS SHALL BE IDENTIFIED IN PULL BOXES, PANEL BOARDS AND CONTRACTORS IDENTIFICATION SHALL MATCH PANEL BOARD SCHEDULE
- 17. THE CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH THE EXISTING CONDITIONS AND THE COORDINATION OF THE WORK, ANY OMISSIONS OR CONFLICT IN THE WORKING DRAWINGS OR BETWEEN THE DRAWINGS AND EXISTING FIELD CONDITIONS WHICH MAY INTERFERE WITH THE PROPER EXECUTION AND COMPLETION OF THE DESCRIBED WORK SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH THE WORK.
- 18. TWO WEEKS AFTER JOB COMPLETION, THE CONTRACTOR SHALL PERFORM ONE NIGHT CHECK OF LIGHTS WITH ENGINEER. REPAIR OR REPLACE NON-FUNCTIONING LUMINARIES AND NOTIFY THE CITY.
- 19. CONTRACTOR SHALL TAKE ALL NECESSARY STEPS TO PREVENT OBJECTIONABLE BLOWING OR DRIFTING OF DIRT, SOIL, OR OTHER DEBRIS DURING EXCAVATION AND INSTALLATION OF ELECTRICAL CONDUIT.
- 20. THE CONTRACTOR SHALL LEAVE THE SITE CLEAN AND ORDERLY AT THE END OF EACH WORKDAY
- 21. ALL MATERIALS AND EQUIPMENT SHALL BE STORED AND INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS UNLESS OTHERWISE NOTED.
- 22. CONTRACTOR TO SUBMIT SHOP DRAWINGS & CATALOG NUMBERS FOR ALL NEW MATERIAL FOR APPROVAL BY THE ELECTRICAL CONSULTANT PRIOR TO CONSTRUCTION
- 23. EVERY ATTEMPT SHALL BE MADE TO PROTECT ALL EQUIPMENT & MATERIAL FROM ANY DAMAGE DURING TRANSPORTATION, LOADING, UNLOADING, AND INSTALLATION AT THE SITE.
- 24. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOST, STOLEN OR DAMAGED EQUIPMENT OR MATERIAL.
- 25. ALL EQUIPMENT INSTALLED OUTSIDE OR EXPOSED TO WEATHER SHALL BE NEMA TYPE 4X UNLESS NOTED OTHERWISE.
- 26. ALL GRASS AREAS AFFECTED BY CONSTRUCTION SHALL BE RE-SODDED TO MATCH THE EXISTING (EX. ZOYSIA, ST. AUGUSTINE).
- 27. THE CONTRACTOR SHALL TAKE SPECIAL NOTE OF SOIL CONDITIONS THROUGHOUT THIS PROJECT. ANY SPECIAL SHORING, SHEETING OR OTHER PROCEDURES NECESSARY TO PROTECT ADJACENT PROPERTY, PUBLIC OR PRIVATE, DURING THE EXCAVATION OF SUBSOIL MATERIAL AND EXFILTRATION TRENCH, OR FILLING OF ANY AREA, OR FOR ANY OPERATION DURING CONSTRUCTION, SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

- 28. THE CONTRACTOR SHALL RESTRICT PERSONNEL, THE USE OF EQUIPMENT, AND THE STORAGE OF MATERIALS LIMITS OF CONSTRUCTION AND DESIGNATED STAGING AREA.
- 29. ALL EXCESS MATERIAL IS TO BE REMOVED AND DISPOSED BY THE CONTRACTOR WITHIN 72 HOURS OF BEING DEPOSITED IN THE CONSTRUCTION PROJECT LIMITS. CONTRACTOR SHALL INCUR ALL COSTS FOR DISPOSAL.
- 30. DISPOSAL OF ALL MATERIALS, RUBBISH, AND DEBRIS SHALL BE MADE AT A LEGAL DISPOSAL SITE OR BY OTHER PRIOR APPROVED MANNER. MATERIAL CLEARED FROM THE SITE AND DEPOSITED ON ADJACENT OR NEARBY PROPERTY WILL NOT BE CONSIDERED AS HAVING BEEN DISPOSED OF SATISFACTORILY.
- 31. WHEN DISSIMILAR MATERIAL CONNECTIONS ARE MADE, SUCH AS CONCRETE TO METAL, THE DISSIMILAR MATERIAL SHALL BE SEPARATED BY COATING THE CONTACT SURFACE WITH BITUMASTIC MATERIAL.
- 32. THE INFORMATION PROVIDED IN THESE DRAWINGS IS SOLELY TO ASSIST THE CONTRACTOR IN ASSESSING THE NATURE AND EXTENT OF CONDITIONS WHICH WILL BE ENCOUNTERED DURING THE COURSE OF WORK. THE CONTRACTORS ARE DIRECTED. PRIOR TO BIDDING. TO CONDUCT WHATEVER INVESTIGATIONS THEY DEEM NECESSARY TO ARRIVE AT THEIR OWN CONCLUSIONS REGARDING THE ACTUAL CONDITIONS THAT WILL BE ENCOUNTERED AND UPON WHICH BIDS WILL BE BASED.
- 33. OPERATING INSTRUCTIONS: UPON COMPLETION OF ALL WORK AND OF ALL TESTS, FURNISH THE NECESSARY SKILLED LABOR AND HELPERS, FOR OPERATING ALL ELECTRICAL SYSTEMS AND EQUIPMENT IN ORDER TO INSTRUCT AND TRAIN THE OWNERS' REPRESENTATIVES IN THE OPERATION AND MAINTENANCE OF ALL EQUIPMENT FURNISHED.
- 34. OPERATION AND MAINTENANCE MANUALS: WITHIN 30 DAYS AFTER THE DATE OF SYSTEM ACCEPTANCE, THE CONTRACTOR SHALL PROVIDE TO THE OWNER, OPERATION AND MAINTENANCE MANUALS CONTAINING SUBMITTAL DATA STATING EQUIPMENT RATING, SELECTED OPTIONS AND REQUIRED MAINTENANCE ACTIONS FOR EACH PIECE OF EQUIPMENT REQUIRING MAINTENANCE THE CONTRACTOR SHALL ALSO PROVIDE THE NAME AND ADDRESS OF AT LEAST ONE QUALIFIED SERVICE AGENCY.
- 35. RECORD DRAWINGS: THE CONTRACTOR IS RESPONSIBLE FOR ALL AS-BUILT DRAWINGS, WHICH SHALL BE PROVIDED TO THE OWNER WITHIN 30 DAYS AFTER THE DATE OF SYSTEM ACCEPTANCE. THEY SHALL INCLUDE A ACTUAL CONDUIT RUNS, PULL BOX LOCATIONS, AND ANY AND ALL EQUIPMENT THAT IS PROVIDED AND INSTALLED AS PART OF THIS PROJECT INDICATING AN ACCURATE DEPICTION OF ALL INSTALLED ELECTRICAL EQUIPMENT.
- 36. BRANCH CIRCUIT VOLTAGE DROP: CONTRACTOR TO VERIFY THAT THE VOLTAGE DROP FOR ALL THE BRANCH CIRCUITS DOES NOT EXCEED 3% OF THE HOMERUN CIRCUITS ORIGINAL VOLTAGE AND TO INCREASE THE WIRE SIZE AS NECESSARY TO ADJUST FOR THE VOLTAGE
- 37. UNGROUNDED CONDUCTORS SHALL USE BLACK INSULATION, NEUTRAL CONDUCTORS SHALL USE WHITE INSULATION, & GROUNDING CONDUCTORS SHALL USE GREEN INSULATION.
- 38. ALL EXPOSED OR SURFACE MOUNTED CONDUIT SHALL BE RIGID GALVANIZED STEEL CONDUIT.
- 39. ALL CONDUIT THAT WILL REMAIN EMPTY AS SPARES SHALL BE MANDREL TESTED, CLEANED INSIDE AND BOTH ENDS CAPPED. LEAVE CORROSION RESISTANT, PULL/DRAG WIRE AND PLACE DUCT MARKERS, OR PULLBOXES TO MARK THE LOCATION OF THE ENDS OF THE CONDUIT
- 40. PULL BOXES SHALL BE LOCATED AT ENDS OF CONDUIT CROSSING ROADWAYS, AND AS NECESSARY FOR THE COMPLETION OF THE PROJECT. INSTALL WITH A 12" BED OF PEAROCK OR CRUSHED STONE FOR DRAINAGE.
- 41. THESE PLANS REPRESENT MINIMUM ACCEPTABLE CRITERIA. THE INSPECTION PER THESE DRAWINGS REPRESENT THE MINIMUM BASE **ACCEPTANCE**
- 42. TRAIL TO REMAIN ACCESSIBLE TO PEDESTRIANS AT ALL TIMES DURING CONSTRUCTION. PROVIDE A MINIMUM OF 4FT OF UNOBSTRUCTED PATH AROUND WORK ZONES. IF 4FT OF UNOBSTRUCTED PATH CANNOT BE MAINTAINED, PROVIDE TEMPORARY PATH AROUND WORKZONE OR PROVIDE PEDESTRIAN DETOURS AS REQUIRED.
- 43. THE FILL MATERIALS WITHIN THE CANAL RIGHT-OF-WAY SHOULD CONSIST OF THE LIMEROCK BASE FILL MATERIAL THAT IS FREE OF CONTAMINANTS AND MEETS THE CLEAN FILL CRITERIA DEFINITION PURSUANT TO CHAPTER 24-5 OF THE CODE OF MIAMI-DADE COUNTY. THE LIMEROCK BASE FILL MATERIAL ALSO SHOULD MEET THE REQUIREMENTS OF THE FDOT STANDARD SPECIFICATIONS, DATED FY 2025-26 OR THE CURRENT AVAILABLE STANDARD SPECIFICATIONS AT THE TIME OF CONSTRUCTION, SECTIONS 911-1 THROUGH 911-2.3, AND 911-3.1 THROUGH 911-3.4.

REVISIONS DATE DESCRIPTION

JOSEPH M. CALDERON TORRES II. P.E. P.E. LICENSE NUMBER 90625 HW LOCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



GENERAL NOTES

SHEET

I:\MIA\PRJ\000021994\700 CADD\Lighting\Turnpike Trail\GNNTLT01.dwd

SPECIAL NOTES

- 1. THE ELECTRICAL CONTRACTOR SHALL VERIFY ALL UTILITIES BY ELECTRONIC METHODS AND PRE-TRENCHING IN COORDINATION WITH ALL UTILITY COMPANIES, PRIOR TO BEGINNING ANY CONSTRUCTION OPERATIONS.
- 2. THE CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT ALL EXISTING UNDERGROUND AND ABOVE GROUND IMPROVEMENTS SUCH AS CONDUITS, GAS MAINS, SANITARY SEWER LINES, TV CABLE, TELEPHONE, LATERALS, WATER MAINS, POLES, PIPES, CABLES AND OTHER STRUCTURES FROM INJURY, AND IN CASE OF DAMAGE THEY SHALL BE RESTORED WITHOUT COMPENSATION.
- 3. HAND-DIG WHERE THERE IS ANY CONFLICT WITH THE EXISTING UNDERGROUND UTILITIES.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTACT ALL UTILITY COMPANIES FOR LOCATION OF THEIR EXISTING FACILITIES. IT'S THE CONTRACTOR'S RESPONSIBILITY TO LOCATE THESE UTILITIES FOR THE EXACT DEPTH. CONTACT "SUNSHINE"AT 811 PRIOR TO
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL DAMAGES SUSTAINED OR COST INCURRED BECAUSE OF THE CONTRACTOR'S OPERATION IN THE VICINITY OF EXISTING UTILITIES OR STRUCTURES. THE CONTRACTOR SHALL NOTIFY THE APPROPRIATE UTILITY COMPANIES WHEN THEIR EXISTING FACILITIES CONFLICT WITH THE CONSTRUCTION.
- 6. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE TO CONTACT/LOCATE OTHER UTILITIES NOT SUBSCRIBING TO "SUNSHINE".
- 7. CONTRACTOR TO USE CAUTION WHEN WORKING UNDER AND IN THE VICINITY OF OVERHEAD AND UNDERGROUND UTILITIES. PROVIDE A LETTER FROM FPL APPROVING METHOD OF LIGHT POLE INSTALLATION. CONTACT JESSICA SALAZAR AT JESSICA.SALAZAR@FPL.COM PRIOR TO CONSTRUCTION.
- 8. LIGHT POLE USED AS BASIS OF DESIGN IS HAPCO'S ROUND TAPERED ALUMINUM (RTA) POLE, OR APPROVED EQUAL. POLES SHALL BE DIRECT BURIED AS PER MANUFACTURER'S RECOMMENDATION AND DESIGNED FOR A WIND SPEED ACCORDING TO THE 2020 FLORIDA
- 9. CONTRACTOR IS TO REMOVE ALL SHRUBS/BUSHES WITHIN A 4 FT RADIUS OF ALL LIGHT POLE LOCATIONS TO ALLOW ADEQUATE SPACE FOR ACCESS AND MAINTENANCE. TRIM TREE BRANCHES WITHIN 2 FT RADIUS OF ALL LIGHT POLE LOCATIONS. VERIFY OWNERSHIP AND COORDINATE REMOVAL AND TRIMMING OF BUSHES, SHRUBS, AND TREES WITH OWNER. REPLACE ANY REMOVED TREES, BUSHES, AND SHRUBS IN KIND.

GUARANTEE

THE CONTRACTOR SHALL SUBMIT A WRITTEN GUARANTEE COVERING ALL MATERIALS, WORKMANSHIP, AND EQUIPMENT FOR A PERIOD OF ONE (1) YEAR COMMENCING FROM THE DAY OF FINAL ACCEPTANCE. ANY REPAIRS DUE TO DEFECTIVE WORKMANSHIP OR MATERIALS DURING THE ONE-YEAR PERIOD SHALL BE MADE BY THE CONTRACTOR WITHOUT CHARGE TO THE CITY.

REVISIONS DATE DESCRIPTION

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 HW INCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



GENERAL NOTES


SHEET


Hernandez, Kevin


Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025


CITY OF DORAL


I:\MIA\PRJ\000021994\700_CADD\Lighting\Turnpike Trail\GNNTLT02.dwg




















REVISIONS		
DATE DESCRIPTION		
	<u> </u>	Lochner

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS

Hernandez, Kevin



TYPICAL SECTIONS

CITY OF DORAL

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025

LEGEND

DESCRIPTION SYMBOLS



POST TOP LIGHT POLE WITH 54W LED LUMINAIRE DESIGNED FOR 5,983 LUMENS, TYPE IV DISTRIBUTION, 4000K CCT, AND WIRED FOR 240V OPERATION. USE LITHONIA'S RADIAN POST TOP LED WITH CURVE RADPT_LED_P3_40K_PATH_HS. LUMINAIRES TO BE EQUIPPED WITH HOUSE SIDE SHIELDS.



POST TOP LIGHT POLE WITH 86W LED LUMINAIRE DESIGNED FOR 9,209 LUMENS, TYPE IV DISTRIBUTION, 4000K CCT, AND WIRED FOR 240V OPERATION. USE LITHONIA'S RADIAN POST TOP LED WITH CURVE RADPT_LED_P4_40K_PATH_HS. LUMINAIRES TO BE EQUIPPED WITH HOUSE SIDE SHIELDS.



EXISTING POLE LIGHT TO REMAIN



EXISTING SOLAR POWERED LIGHT POLE TO BE REMOVED AND DISPOSED.



EXISTING LIGHT POLE AND FOUNDATION TO BE REMOVED AND DISPOSED.



PROPOSED LOAD CENTER



EXISTING LOAD CENTER



2" SCHEDULE 40 PVC CONDUIT, DIRECT BURIED IN OPEN TRENCH, CONTAINING CIRCUIT CONDUCTORS AS INDICATED ON PLANS. ALL CONDUCTORS SHALL BE STRANDED COPPER WITH THWN-2 INSULATION. GROUND CONDUCTORS SHALL HAVE GREEN COLOR INSULATION. RUN GROUND CONDUCTORS WITH OTHER CONDUCTORS.



2" HDPE CONDUIT INSTALLED BY DIRECTIONAL BORE, CONTAINING CIRCUIT CONDUCTORS AS INDICATED ON PLANS. ALL CONDUCTORS SHALL BE STRANDED COPPER WITH THWN-2 INSULATION. GROUND CONDUCTORS SHALL HAVE GREEN COLOR INSULATION. RUN GROUND CONDUCTORS WITH OTHER CONDUCTORS.



PULL BOX

1. COORDINATE LIGHT POLE AND LUMINAIRE COLORS WITH THE CITY OF DORAL PRIOR TO PROCUREMENT.

REVISIONS DATE DESCRIPTION

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



SIDEWALKS AND SHARED USE PATH

LIGHTING CRITERIA (TURNPIKE TRAIL)

2.5 FOOT CANDLES 4:1 OR LESS 10:1 OR LESS

160 MPH

AVERAGE INITIAL INTENSITY UNIFORMITY RATIO AVG./MIN.

UNIFORMITY RATIO MAX./MIN.

WIND SPEED

LE GEND

SHEET

Hernandez, Kevin

I:\MIA\PRJ\000021994\700_CADD\Lighting\Turnpike Trail\GNNTLT03.dwg

CITY OF DORAL Public Works Department

Public Works Department
Permit #PWUT-2505-0061
RECEIVED: 05/06/2025

																					F E1	111111 #P VV U 1-23
Pole							Arm	Arm	Mount	Quantity		Make\		IES Dist		Tilt	Luminaire	Luminaire	Load Center	Circuit	M RE	CEIVED: 05/0
No.	Easting	Northing	Baseline	Station	Offset	Foundation	Length	Rise	Height	Luminaires	Туре	Model	Lumens	Туре	CCT(K)	(deg)	Watts	Volts	No.	No.	Ag ene,	1 47 100
P-1	858961.098	532446.315	NW 25TH ST	14+93.57	38.47' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-2	858901.098	532446.198	NW 25TH ST	14+33.57	38.74' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-3	858841.098	532446.081	NW 25TH ST	13+73.57	39.02' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-4	858781.098	532445.964	NW 25TH ST	13+13.57	39.29' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-5	858721.099	532445.847	NW 25TH ST	12+53.58	39.56' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-6	858661.099	532445.731	NW 25TH ST	11+93.58	39.84' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-7	858601.099	532445.614	NW 25TH ST	11+33.58	40.11' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-8	858541.099	532445.497	NW 25TH ST	10+73.58	40.39' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-9	858509.8	532471.339	NW 117TH AVE	10+65.39	44.03' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-10	858505.945	532537.011	NW 117TH AVE	11+31.15	42.18' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-11	858503.905	532602.98	NW 117TH AVE	11+97.15	42.16' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-12	858501.831	532668.948	NW 117TH AVE	12+63.15	42.10' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-13	858499.909	532734.919	NW 117TH AVE	13+29.15	42.19' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-14	858498.647	532796.648	NW 117TH AVE	13+90.89	42.82' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-15	858496.277	532872.317	NW 117TH AVE	14+66.60	42.76' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-16	858494.163	532927.859	NW 117TH AVE	15+22.18	42.34' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-17	858492.552	532985.595	NW 117TH AVE	15+79.94	42.49' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-18	858490.818	533038.31	NW 117TH AVE	16+32.68	42.37' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-19	858488.666	533106.276	NW 117TH AVE	17+00.68	42.29' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-20	858486.501	533174.241	NW 117TH AVE	17+68.68	42.20' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-21	858484.315	533242.206	NW 117TH AVE	18+36.68	42.09' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-22	858482.133	533310.171	NW 117TH AVE	19+04.68	41.99' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-23	858480.142	533378.142	NW 117TH AVE	19+72.68	42.07' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-24	858478.149	533446.113	NW 117TH AVE	20+40.68	42.16' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-25	858476.14	533514.083	NW 117TH AVE	21+08.68	42.22' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-26	858474.131	533582.053	NW 117TH AVE	21+76.68	42.29' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-27	858472.12	533650.024	NW 117TH AVE	22+44.68	42.35' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-28	858469.69	533717.98	NW 117TH AVE	23+12.68	42.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-29	858467.522	533785.945	NW 117TH AVE	23+80.68	41.91' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	1	Doral	715-516-110
P-30	858465.355	533853.91	NW 117TH AVE	24+48.68	41.82' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-31	858463.246	533921.878	NW 117TH AVE	25+16.68	41.78' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-32	858461.215	533989.847	NW 117TH AVE	25+84.68	41.83' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-33	858459.183	534057.817	NW 117TH AVE	26+52.68	41.87' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-34	858457.151	534125.787	NW 117TH AVE	27+20.68	41.92' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-35	858455.12	534193.757	NW 117TH AVE	27+88.68	41.96' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-36	858453.088	534261.726	NW 117TH AVE	28+56.68	42.01' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-37	858450.879	534329.69	NW 117TH AVE	29+24.68	41.87' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-38	858448.666	534397.654	NW 117TH AVE	29+92.68	41.74' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-39	858446.689	534465.625	NW 117TH AVE	30+60.68	41.84' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-40	858444.905	534533.601	NW 117TH AVE	31+28.68	42.13' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-41	858442.889	534601.571	NW 117TH AVE	31+96.68	42.19' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-42	858440.746	534669.537	NW 117TH AVE	32+64.68	42.12' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-43	858438.633	534737.504	NW 117TH AVE	33+32.68	42.08' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-44	858436.648	534805.475	NW 117TH AVE	34+00.68	42.18' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-45	858434.625	534873.445	NW 117TH AVE	34+68.68	42.23' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-46	858432.537	534941.413	NW 117TH AVE	35+36.68	42.22' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-47	858430.304	535009.377	NW 117TH AVE	36+04.68	42.06' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-48	858428.027	535077.339	NW 117TH AVE	36+72.68	41.86' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-49	858425.933	535145.306	NW 117TH AVE	37+40.68	41.84' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110
P-50	858424.325	535206.583	NW 117TH AVE	38+01.97	42.10' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	1	Doral	715-516-110

Lighting Data Table

	REVISIONS					
DATE	DESCRIPTION					
		6	1	LO	ch	n

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



POLE DATA

SHEET NO.

L-10

CITY OF DORAL Public Works Department

Public Works Department
Permit #PWUT-2505-0061
RECEIVED: 05/06/2025

																				1		111111 #P VV U 1-23
Pole	Facting	Northing	5 "	6	0.66		Arm	Arm	Mount	Quantity	Type	Make\	,	IES Dist	CCT(K)	Tilt	Luminaire	Luminaire	Load Center	Circuit	M RE	CEIVED: 05/0
No. P-51	Easting 858422.836	Northing 535267.621	Baseline NW 117TH AVE	Station 38+63.03	0ffset 42.48' RT	Foundation DIRECT	Length N/A	Rise N/A	Height 10'	Luminaires 1		Model RADPT	Lumens 5983	Type	CCT(K) 4000K	(deg) 0	Watts 54	Volts 240V	No.	No.	Doral	715-516-110
P-52	858420.895	535348.231	NW 117TH AVE	39+43.66	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-53	858419.185	535404.205	NW 117TH AVE	39+99.66	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-54	858417.402	535464.407	NW 117TH AVE	40+59.89	43.06' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-55	858415.817	535516.155	NW 117TH AVE	41+11.66	43.05' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-56	858414.138	535572.13	NW 117TH AVE	41+67.66	43.08' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-57	858412.417	535628.103	NW 117TH AVE	42+23.66	43.07' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-58	858410.676	535684.076	NW 117TH AVE	42+79.66	43.04' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-59	858408.935	535740.049	NW 117TH AVE	43+35.66	43.01' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-60	858407.071	535790.445	NW 117TH AVE	43+86.09	42.68' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-61	858405.508	535850.969	NW 117TH AVE	44+46.63	42.97' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-62	858403.798	535907.971	NW 117TH AVE	45+03.66	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-63	858401.858	535966.926	NW 117TH AVE	45+62.65	42.86' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-64	858399.919	536027.027	NW 117TH AVE	46+22.78	42.76' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-65	858398.669	536080.846	NW 117TH AVE	46+76.61	43.15' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-66	858396.781	536141.365	NW 117TH AVE	47+37.16	43.11' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-67	858395.078	536197.339	NW 117TH AVE	47+93.16	43.12' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-68	858393.492	536252.609	NW 117TH AVE	48+48.45	43.22' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-69	858391.946	536295.748	NW 117TH AVE	48+91.62	42.99' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-70	858390.243	536351.723	NW 117TH AVE	49+47.62	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-71	858388.54	536407.697	NW 117TH AVE	50+03.62	43.01' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-72	858386.28	536473.445	NW 117TH AVE	50+69.41	42.75' RT	DIRECT	N/A	N/A	10'	I	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-73	858384.561	536529.418	NW 117TH AVE	51+25.41	42.75' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-74	858382.842	536585.392	NW 117TH AVE	51+81.41	42.74' RT	DIRECT	N/A	N/A	10'	I	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-75 P-76	858381.582 858380.149	536635.632 536687.592	NW 117TH AVE	52+31.66 52+83.64	43.01' RT	DIRECT DIRECT	N/A N/A	N/A	10'	1	POST TOP	RADPT RADPT	5983 5983	IV IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-70 P-77	858377.537	536747.556	NW 117TH AVE	53+43.66	43.16' RT 42.38' RT	DIRECT	N/A N/A	N/A N/A	10'	1	POST TOP	RADPT	5983	IV	4000K 4000K	0	54	240V 240V	B B	2	Doral Doral	715-516-110
P-78	858374.811	536809.237	NW 117TH AVE	54+05.39	42.56 RT	DIRECT	N/A N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-79	858373.268	536866.648	NW 117TH AVE	54+62.82	41.75' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-80	858372.25	536915.465	NW 117TH AVE	55+11.65	42.23' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-81	858370.946	536971.45	NW 117TH AVE	55+67.65	42.63' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-82	858369.604	537027.433	NW 117TH AVE	56+23.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-83	858367.895	537083.407	NW 117TH AVE	56+79.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-84	858366.185	537139.381	NW 117TH AVE	57+35.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-85	858364.475	537195.355	NW 117TH AVE	57+91.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-86	858362.765	537251.329	NW 117TH AVE	58+47.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-87	858361.056	537307.303	NW 117TH AVE	59+03.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-88	858359.346	537363.277	NW 117TH AVE	59+59.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-89	858357.636	537419.251	NW 117TH AVE	60+15.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-90	858355.927	537475.225	NW 117TH AVE	60+71.65	43.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-91	858354.293	537531.201	NW 117TH AVE	61+27.65	43.08' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	2	Doral	715-516-110
P-92	858347.872	537963.157	NW 117TH AVE	65+59.60	49.83' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	В	2	Doral	715-516-110
P-93	858337.631	538032.042	NW 117TH AVE	66+28.76	41.70' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-94	858328.921	538095.523	NW 117TH AVE	66+92.48	34.93' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-95	858325.921	538160.553	NW 117TH AVE	67+57.57	33.91' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-96	858323.99	538225.524	NW 117TH AVE	68+22.57	33.96' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-97	858322.097	538290.497	NW 117TH AVE	68+87.57	34.05' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-98	858320.125	538355.467	NW 117TH AVE	69+52.57	34.06' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-99	858318.098	538420.436	NW 117TH AVE	70+17.57	34.01' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-100	858316.072	538485.404	NW 117TH AVE	70+82.57	33.97' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110

Lighting Data Table

R E V I S I O N S

DATE DESCRIPTION



JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



POLE DATA

SHEET NO.

L-11

CITY OF DORAL
Public Works Department
Pormit #DWLIT 2505 0061

715-516-110

715-516-110

715-516-110

										Lighting Data	Table											olic Works Depa mit #PWUT-2505	
Pole No.	Easting	Northing	Baseline	Station	Offset	Foundation	Arm Length	Arm Rise	Mount Height	Quantity Luminaires	Туре	Make∖ Model	Lumens	IES Dist Type	CCT(K)	Tilt (deg)	Luminaire Watts	Luminaire Volts	Load Center No.	Circuit No.		CEIVED: 05/06/2	
P-101	858314.066	538550.373	NW 117TH AVE	71+47.57	33.94' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-102	858312.131	538615.345	NW 117TH AVE	72+12.57	33.99' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-103	858310.192	538680.316	NW 117TH AVE	72+77.57	34.03' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-104	858308.197	538745.285	NW 117TH AVE	73+42.57	34.02' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-105	858306.203	538810.255	NW 117TH AVE	74+07.57	34.01' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-106	858304.21	538875.225	NW 117TH AVE	74+72.57	34.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-107	858302.222	538940.194	NW 117TH AVE	75+37.57	33.99' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-108	858300.254	539005.164	NW 117TH AVE	76+02.57	34.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	
P-109	858298.251	539069.878	NW 117TH AVE	76+67.32	33.97' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110	

POST TOP

POST TOP

POST TOP

RADPT

RADPT

RADPT

5983

IV

IV

IV

4000K

4000K

4000K

0

0

54

86

86

240V

240V

240V

В

В

В

Doral

Doral

P-111 858294.434	539199.927 NW 117TH AVE	77+97.42	34.12' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-112 858292.498	539264.898 NW 117TH AVE	78+62.42	34.17' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-113 858291.032	539330.053 NW 117TH AVE	79+27.59	34.69' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-114 858308.455	539383.115 NW 117TH AVE	79+80.10	53.72' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	В	1	Doral	715-516-110
P-115 858306.993	539433.094 NW 117TH AVE	80+30.10	53.78' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	В	1	Doral	715-516-110
P-116 858305.53	539483.072 NW 117TH AVE	80+80.10	53.85' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-117 858304.068	539533.051 NW 117TH AVE	81+30.10	53.91' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-118 858302.581	539586.468 NW 117TH AVE	81+83.54	54.05' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-119 858302.225	539643.505 NW 117TH AVE	82+40.56	55.43' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-120 858300.462	539710.096 NW 117TH AVE	83+07.17	55.70' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-121 858296.679	539775.073 NW 117TH AVE	83+72.23	53.90' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	В	1	Doral	715-516-110
P-122 858294.247	539839.344 NW 117TH AVE	84+36.55	53.43' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	В	1	Doral	715-516-110

56.02' RT DIRECT N/A10' POST TOP RADPT5983 4000K 54 240V В 715-516-110 N/A1 0 POST TOP RADPT 715-516-110 69.56' RT DIRECT N/AN/A10' 5983 IV 4000K 0 54 240V В Doral 52.65' RT DIRECT N/AN/A10' POST TOP RADPT 5983 4000K 54 715-516-110 POST TOP 52.43' RT DIRECT N/AN/ARADPT 54 715-516-110 10' 5983 IV 4000K 0 240V Doral 52.72' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV 4000K 0 54 240V С 3 715-516-110 52.25' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV 4000K 0 54 240V 715-516-110 Doral 52.61' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV4000K 0 54 240V 715-516-110 52.77' RT DIRECT N/ARADPT N/APOST TOP 5983 54 240V 715-516-110 10' IV 4000K 0 Doral

9209

9209

NW 117TH AVE 93+34.57 53.65' RT DIRECT N/AN/A10' 1 POST TOP RADPT 5983 IV 4000K 0 54 240V С .3 715-516-110 NW 117TH AVE 53.61' RT DIRECT N/AN/A10' POST TOP RADPT 4000K 0 54 С 715-516-110 93+93.69 5983 IV 240V Doral NW 117TH AVE 94+57.74 54.28' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV 4000K 0 54 240V С 715-516-110 NW 117TH AVE 95+19.44 52.36' RT DIRECT N/AN/APOST TOP RADPT 54 715-516-110 10' 5983 IV 4000K 0 240V Doral NW 117TH AVE 95+84.32 52.94' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV 4000K 0 54 240V С 3 715-516-110 NW 117TH AVE 96+48.90 51.97' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV 4000K 0 54 240V С 715-516-110 Doral NW 117TH AVE 97+08.78 52.68' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV 4000K 0 54 240V С 715-516-110 97+66.55 51.49' RT DIRECT N/AN/APOST TOP RADPT 4000K 54 240V 10' 5983 IV0 Doral

541168.666 NW 117TH AVE 715-516-110 541226.608 NW 117TH AVE 98+31.50 51.26' RT DIRECT N/Δ N/Δ 10' 1 POST TOP RADPT 5983 IV 4000K 0 54 240V С Doral 715-516-110 541284.568 NW 117TH AVE 98+82.54 50.30' RT DIRECT N/A10' POST TOP RADPT 5983 IV4000K 0 54 240V 715-516-110 Doral NW 117TH AVE 99+43.64 49.95' RT DIRECT N/AN/A10' POST TOP RADPT 5983 IV 4000K 0 54 240V 715-516-110 NW 117TH AVE POST TOP 541400.498 99+98.54 49.88' RT DIRECT N/AN/A10' RADPT 5983 IV 4000K 0 54 240V Doral 715-516-110 NW 117TH AVE 50.45' RT DIRECT POST TOP RADPT 715-516-110 100+56.53 N/AN/A10' 1 5983 IV 4000K 0 54 240V С Doral NW 117TH AVE 51.01' RT POST TOP RADPT 54 541516.473 101+14.53 DIRECT N/A10' 5983 IV 4000K 0 240V C 715-516-110 541564.368' NW 117TH AVE 51.73' RT DIRECT N/APOST TOP RADPT IV 715-516-110 101+62.43 N/A10' 5983 4000K Ω 54 240V Doral

POST TOP

POST TOP

POST TOP

	REVISIONS	
DATE	DESCRIPTION	
		Lochne

NW 117TH AVE

NW 117TH AVE

NW 117TH AVE

P-110

P-123

P-124

P-125

P-126

P-128

P-129

P-130

P-131

P-132

P-133

P-134

P-135

P-136

P-137

P-138

P-139

P-140

P-141

P-142

P-143

P-144

P - 145

P-146

P-147

P-148

P-149

P-150

858296.37

858292.2

858290.408

858290.981'

858303.33

858276.788

858274.928

858273.496

858271.011

858269.76

858268.041

858267.068

858265.225

858263.943

858260.136

858258.739

858255.797

858254.676

858251.726

858249.508

858246.99

858244.772'

858243.031

858241.825

858240.619

858239.873

858238.666'

858237 093'

858235.290'

539134.955

539903.312

539967.286

540031.269'

540070.803

540386.249

540439.95

540496.254

540562.185

540615.007

540676.402

540736.961

540796.049

540860.087

540921.697

540986.566

541051.087

541110.958

541345.629

541458.486

541622.356'

541680 334'

541743.359'

NW 117TH AVE

77+32.42

85+00.55

85+64.55

86+28.48

86+67.62

89+83.73

90+37.46

90+93.78

91+59.76

92+12.59

92+74.01

102+20.42

102+78 42

103+41.47

52.29' RT

52 49' RT

52.61' RT

DIRECT

DIRECT

DIRECT

N/A

N/A

N/A

N/A

N/A

N/A

10'

10'

10'

34.08' RT

53.33' RT

53.49' RT

DIRECT

DIRECT

DIRECT

N/A

N/A

N/A

N/A

N/A

N/A

10'

10'

10'

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 HW LOCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

1

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*

IV

IV

4000K

4000K

4000K

0

0

54

54

54

240V

240V

240V

POLE DATA

C

SHEET

715-516-110

715-516-110

715-516-110

L-12

RADPT

RADPT

RADPT

5983

5983

5983

Doral

Doral

Lighting Data Table			
	Lighting	Data	Tahle

Polo							Arm	Arm	Mount	Lighting Data Quantity	Table	Make\		IES Dist		Tilt	Luminaire	Luminaire	Load Center	Circuit	P P	ublic Works Departmen ermit #PWUT-2505-0061 ECEIVED: 05/06/2025
Pole No.	Easting	Northing	Baseline	Station	0ff set	Foundation	Length	Rise	Height	Luminaires	Туре	Make\ Model	Lumens	Type	CCT(K)	(deg)	Luminaire Watts	Volts	No.	No.	Ag	202.123.00,00,2020
P-151	858233.486	541806.384	NW 117TH AVE	104+04.52	52.73' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-152	858231.627	541859.351	NW 117TH AVE	104+57.52	52.49' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-153	858229.414	541922.312	NW 117TH AVE	105+20.52	52.20' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-154	858227.353	541980.275	NW 117TH AVE	105+78.52	51.91' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-155	858225.277	542038.238	NW 117TH AVE	106+36.52	51.61' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-156	858223.2	542096.201	NW 117TH AVE	106+94.52	51.30' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-157	858221.123	542154.163	NW 117TH AVE	107+52.52	51.00' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-158	858219.045'	542208.163'	NW 117TH AVE	108+6.56	50.57' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-159	858216.87	542270.085	NW 117TH AVE	108+68.52	50.28' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-160	858214.653	542328.043	NW 117TH AVE	109+26.51	49.84' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-161	858212.436	542386.001	NW 117TH AVE	109+84.51	49.39' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-162	858210.574	542443.971	NW 117TH AVE	110+42.51	49.30' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-163	858208.712	542501.941	NW 117TH AVE	111+00.51	49.21' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-164	858206.85	542559.911	NW 117TH AVE	111+58.51	49.12' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-165	858205.065	542617.884	NW 117TH AVE	112+16.51	49.10' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-166	858203.37	542675.859	NW 117TH AVE	112+74.51	49.18' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-167	858201.675	542733.835	NW 117TH AVE	113+32.51	49.26' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	ن 715-516-110
P-168	858199.955	542791.809	NW 117TH AVE	113+90.51	49.31' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-169	858197.96	542849.775	NW 117TH AVE	114+48.51	49.08' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	1	Doral	715-516-110
P-170	858211.883	542883.491	NW 117TH AVE	114+81.79	64.03' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	С	1	Doral	715-516-110

REVISIONS DATE

4 Lochner

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



POLE DATA

SHEET NO.

L-13


Hernandez, Kevin


I:\MIA\PRJ\000021994\700_CADD\Lighting\Turnpike Trail\PLDTLT01.dwg

CITY OF DORAL

CITY OF DORAL

Public Works Department Permit #PWUT-2505-0061





REVISIONS **Lochner** DATE DESCRIPTION

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178


CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*





PROJECT LAYOUT


SHEET


L-14




































































EQUIPMENT TO METER BASE GROUND LUG FROM SERVICE POINT

TO LIGHTING PANEL

METER SOCKET DETAIL NTS

#6 AWG INSULATED COPPER GROUND WIRE IN 3/4" RIGID GALVANIZED STEEL CONDUIT.

-BRANCH CKT'S IN 2" RIGID GALVANIZED STEEL CONDUIT (FOR NUMBER OF BRANCH CKT'S REFER TO PLANS) -3#2 IN 2" RIGID GALVANIZED STEEL CONDUIT

8'-0"

1#6 GRD. IN 2" PVC CONDUIT

6'-0" -

— 5/8" DIA. X 20'-0" GRD. ROD

CONCRETE-APRON

EXIST. BARE WIRE #6 INHERENT TO THE POLE

-PHOTOCELL SPLICE AND PHOTOCELL WIRE SHALL BE TERMINAL SLEEVE SPLICE

-SERVICE LOAD CENTER IN NEMA 4X ENCLOSURE (FOR NUMBER AND SIZE OF BREAKER

TERMINATE CONDUIT WITH INSULATED GROUNDING

-AT TOP OF POLE THE GROUNDING PIG TAIL MUST BE DETACHED

-METER CAN BY CONTRACTOR, METER BY UTILITY METER TO BE ORIENTED ON SIDE OF CONCRETE POLE SO WHEN READING IT YOU ARE FACING ONCOMING TRAFFIC

PULL BOX (25" X 15 1/2" X 12") -

CONCRETE-

PRESTRESSED CONCRETE POLE TYPE P-II 18'-0" LONG

BUSHING WITH SOLDERLESS LUGS

MAX. 5'-6" ABOVE GRADE

SEE PANEL SCHEDULE).

- AT BOTTOM THE GRD. (PIG TAIL) TO BE CONNECTED TO THE GROUND ROD

COVER MARKED "ELECTRIC" -TERMINATE RIGID STEEL CONDUIT

EXOTHERMICAL CONNECTION

-CONDUIT CLAMP (TYP.)

PULL BOX (25" X 15 1/2" X 12") COVER MARKED "LIGHTING"

3" WARNING TAPE-

-0" BED OF PEAROCK OR CRUSHED STONE FOR DRAINAGE

5/8" DIA, X 40'-0" GRD, ROD

3#2 IN 2" PVC CONDUIT BRANCH CKT'S AND 1#6 GRD. IN 2" PVC CONDUIT TO LIGHT POLE

SERVICE POINT DETAIL

NTS

TRANSITION FITTING FROM RIGID STEEL

TO PVC AFTER 90° RIGID STEEL ELBOW

LOAD CENTER B PANEL BOARD SCHEDULE 10,3W,240/120 V (2P - 100 A MCB) 10,000 RMS SYMETRICAL SURF-MTD SERVING KVA AMPS FUSE WIRE/CONDUCT LIGHTNING PROT. 20 PED. LGT. (TPK) 20 2.2 11.6 6 AWG PED. LGT. (TPK) #6 AWG WITH 11.0 20 #2 HOMERUN

SERVICE ATTACHMENT

BY UTILITY

NUMBERS OF BRANCH CKT. BREAKERS AS REQUIRED

CONTINUOUS LOADS= 4856 VA

Amp = 25.3 A25% CONT. LOAD= 1214 VA

TOTAL= 6070 VA

PHOTOCELL PANELBOARD -LIGHTNING PROTECTOR 0 0 0 0 0 000 MAIN CIRCUIT BREAKER 0 0 DISTRIBUTION PANEL BOARD 000 TERMINAL BLOCK CONTACTOR IN NEMA 1 ENCLOSURE **ा** । 000 HAND OFF AUTO SELECTOR SWITCH -CONTROL POWER TRANSFORMER -DEAD FRONT COVER FRONT VIEW SUBPLATE LAYOUT

> LIGHTING CONTROL CENTER NTS

NOTES:

- 1. ALL WIRES EXTERNAL TO CONTROL CABINET TO BE TERMINATED TO A TERMINAL.
- 2. PROVIDE SIGNED AND SEALED STRUCTURAL PLANS AND CALCULATIONS FOR THE PRESTRESSED CONCRETE POLE.
- 3. PROVIDE ALUMINUM METER APPROVED BY FPL WITH A GROUND LUG, BYPASS MECHANISM WITH LEVER AND ISOLATED NEUTRAL

REVISIONS DATE DESCRIPTION

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 HW LOCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178


CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



SERVICE POINT ELECTRICAL DE TAILS

L-37

SHEET



ISOLATED FROM SERVICE POINT

EQUIPMENT GROUND WIRE FOVE

BOND BUSHING TO METER BASE

TO LIGHTING PANEL

METER SOCKET DETAIL

NTS

PRESTRESSED CONCRETE POLE, TYPE — P-V, 50FT PER FDOT STANDARD INDEX 641-010

MINIMUM LENGTH OF 10 FEET SHALL BE PROVIDED
FOR EACH WEATHER HEAD CONDUCTOR.
CONTRACTOR SHALL COORDINATE WITH THE UTILITY COMPANY
FOR MOUNTING HEIGHT REQUIREMENTS, AND CONNECTION.
OVERHEAD CROSSING SHALL MAINTAIN MINIMUM CLEARANCE
OF 40' FROM GRADE AT MAXIMUM POINT OF SAG

PHOTOCELL SPLICE AND PHOTOCELL WIRE— SHALL BE TERMINAL SLEEVE SPLICE

SERVICE LOAD CENTER IN NEMA 4X ENCLOSURE -(FOR NUMBER AND SIZE OF BREAKER SEE PANEL SCHEDULE)

TERMINATE CONDUIT WITH INSULATED GROUNDING BUSHING WITH SOLDERLESS LUGS

#6 INSULATED COPPER GROUND WIRE IN 3/4" — RIGID GALVANIZED STEEL CONDUIT

PULL BOX (25" X 15 1/2" X 12")

COVER MARKED "LIGHTING"

BRANCH CKT. IN 2" RIGID GALVANIZED STEEL CONDUIT (FOR NUMBER OF BANCH CKT'S REFER TO PLAN).

CONCRETE

1'-0" BED OF PEAROCK OR CRUSHED

STONE FOR DRAINAGE.

GROUND

BRANCH CKT'S AND 1#6 GRD.
IN 2" COND. TO LIGHTING POLE

SERVICE POINT DETAIL
NTS

PHOTOCELL - PANELBOARD -LIGHTNING PROTECTOR 0 000 MAIN CIRCUIT BREAKER 0 0 DISTRIBUTION PANEL BOARD 000 TERMINAL BLOCK CONTACTOR IN NEMA 1 ENCLOSURE 000 000 - HAND OFF AUTO SELECTOR SWITCH 0 .||||||. -CONTROL POWER TRANSFORMER 0 -DEAD FRONT COVER FRONT VIEW SUBPLATE LAYOUT

NTS

LIGHTING CONTROL CENTER NTS

NOTES:

- 1. ALL WIRES EXTERNAL TO CONTROL CABINET TO BE TERMINATED TO A TERMINAL.
- 2. PROVIDE SIGNED AND SEALED STRUCTURAL PLANS AND CALCULATIONS FOR THE PRESTRESSED CONCRETE POLE.
- 3. PROVIDE ALUMINUM METER APPROVED BY FPL WITH A GROUND LUG, BYPASS MECHANISM WITH LEVER AND ISOLATED NEUTRAL
- 4. PROVIDE SHOP DRAWING SUBMITTAL FOR PRESTRESSED CONCRETE POLE. INCLUDE CONCRETE POLE CALCULATIONSSIGNED BY AN ENGINEER.

NEMA-1 10,3W,240/120 V (2P - 100 A MCB) 10,000 RMS SYMETRICAL SURF-MTD CKT NO SERVING KVA AMPS FUSE WIRE/CONDUCT A-0 LIGHTNING PROT. 20 A-1 PED. LGT. (TPK)
25TH TO 34TH 3.1 12.8 20 #2 AWG A-2 PED. LGT. (BCN)
GLRY TO E 0F 112 2.7 11.5 20 #8 AWG

LOAD CENTER A PANEL BOARD SCHEDULE

5/8" DIA. X 20'-0" GRD ROD

NUMBERS OF BRANCH CKT. BREAKERS AS REQUIRED

2.8 | 11.8

20

CONTINUOUS LOADS= 8631 VA 25% CONT. LOAD= 2158 VA

PED. LGT. (BCN)

A-3

TOTAL= 10789 VA

LOAD CENTER C PANEL BOARD SCHEDULE 10,3W,240/120 V (2P - 100 A MCB) 10,000 RMS SYMETRICAL SURF-MTD SERVING KVA AMPS FUSE WIRE/CONDUCT C-0LIGHTNING PROT 20 PED. LGT. (TPK) 1.9 7.90 C-1 20 #8 AWG LC-C TO 58TH PED. LGT. (DRES) 117TH TO 114TH #6 AWG WITH #4 HOMERUN 6.7 20 PED. LGT. (TPK) LC-C TO 50TH C-3 0.8 3.25 20 #8 AWG

NUMBERS OF BRANCH CKT. BREAKERS AS REQUIRED

CONTINUOUS LOADS= 4269 VA

DISTRIBUTION LINE

UTILITY TRANSFORMER

ONCOMING TRAFFIC

MAX. 5'-6" ABOVE GRADE

-SERVICE LOAD CENTER

240V/120V, 1 PHASE, 3W

UTILITY POLE

- 3#2/0 AWG & 1 #2 GND IN 2" COND.

METER CAN BY CONTRACTOR, METER BY UTILITY.

METER TO BE ORIENTED ON SIDE OF CONCRETE

POLE SO WHEN READING IT YOU ARE FACING

25% CONT. LOAD= 1067 VA Amp= 22.2 A

TOTAL= 5336 VA

DATE DESCRIPTION

PLOCHNET

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



SERVICE POINT ELECTRICAL DETAILS

L-38

SHEET

CITY OF DORAL
Public Works Department
Permit #PWUT-2505-0061

RECEIVED: 05/06/2025


Hernandez, Kevin

4/8/2025 11:27:34 AM

#2 AWG

Amp= 45.0 A

I:\MIA\PRJ\000021994\700_CADD\Lighting\Turnpike Trail\SPDTLT01.dwg



BOND LIGHT POLE METAL TO GROUND -CONDUCTORS, FOR SPLICE (GELCAP) -SIZE AND QUANTITY SEE EXOTHERMIC — PLANS CONNECTION 13" X 24" X 12" -PULL BOX 12" BED OF -PEAROCK OR CRUSHED STONE FOR DRAINAGE STRAIN RELIEF FITTINGS 5" DIA. X 20' LONG GROUND ROD PULL BOX DETAIL

LIGHT POLE DETAIL

REVISIONS	
DATE DESCRIPTION	
	ے Lochner

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



LIGHT POLE DETAIL

SHEET NO.	
L-39	


INDEX OF LIGHTING PLANS


SHEET NO. SHEET DESCRIPTION L-1 KEYSHEET L-2 - L-3 TABULATION OF QUANTITIES L-4 - L-5 GENERAL NOTES TYPICAL SECTIONS L-6 LEGEND L-7 POLE DATA L-8 - L-9 L-10 PROJECT LAYOUT L-11 - L-18 LIGHTING PLAN L-19 LIGHT POLE DETAIL

CITY OF DORAL, FLORIDA

TRAIL LIGHTING IMPROVEMENT PLANS

BEACON TRAIL ALONG NW 25TH ST FROM EAST OF NW 117TH AVE TO WEST OF NW 107TH AVE.





THIS ITEM HAS BEEN DIGITALLY SIGNED AND SEALED BY

Joseph M Calderon Torres 2025.04.08 14:53:42-04'00'

ON THE DATE ADJACENT TO THE SEAL

PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES

LIGHTING PLANS ENGINEER OF RECORD:

JOSEPH M. CALDERON TORRES II, P.E. P.E. NO.: 90625 H.W. LOCHNER, INC 8750 N.W. 36TH STREET, SUITE 360 MIAMI, FLORIDA 33178 TEL: (305) 503-9873; FAX: (305) 503-9882 VENDOR NO.: VF-362-338-11

PERMIT SUBMITTAL

SHEET NO.

L-1

GOVERNING STANDARD PLANS:

Florida Department of Transportation, FY2025-26 Standard plans for Road and Bridge Construction and applicable Interim Revisions (Irs).

Standard Plans for Road Construction and associated Irs are available at the following website:

http://www.fdot.gov/design/Standardplans.shtm

APPLICABLE IRs: N/A

Standard Plans for Bridge Construction are included in the Structures Plans Component.

GOVERNING STANDARD SPECIFICATIONS: Florida Department of Transportation, FY 2025-26 Standard Specifications for Road and Bridge Construction at the following

http://www.fdot.gov/programmanagement/Implemented/SpecBooks

TABULATION

		CITY OF DORAL
		Public Works Department Permit #PWUT-2505-0061
OF QUANTITIES		RECEIVED: 05/06/2025
SHEET NUMBERS	TOTAL	GRAND

D 41/								SHEET NUMB	ERS							TAL \coprod	GEIVED	AND
PAY ITEM	DESCRIPTION	UNIT	L -	11 L-12		L	- 13	L - 14		L - 15		L - 16		- 17		IS EET		TAL
NO.			PLAN	FINAL	PLAN FINA	AL PLAN	FINAL	PLAN FIN	IAL PLA	AN FINAL	PLAN	V FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL
630-2-11	CONDUIT, FURNISH & INSTALL, OPEN TRENCH	LF	527		440	570		401	56	5	566		572		3642			
630 - 2 - 12	CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE	LF			62			161							223			
635 - 2 - 11	PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE	EA	8		10	8		7	8		8		8		57			
715-1-12	LIGHTING CONDUCTORS, F&I, INSULATED, NO.8 - 6	LF	2229		1470	1644		1374							6717			
715-1-13	LIGHTING CONDUCTORS, F&I, INSULATED, NO.4 - 2	EA			1992	2358		2202	227	4	2274		2274		13374			
715-516-110	LIGHT POLE COMPLETE, DIRECT BURIED, F&I, POLE TOP MOUNT, 10'	EA	9		10	8		7	8		8		8		58			
																		
															1			

	REVISIONS	
DATE	DESCRIPTION	
		Lochno

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



TABULATION OF QUANTITIES

SHEET NO.

Hernandez, Kevin

I:\MIA\PRJ\000021994\700_CADD\Lighting\Beacon Trail\TABQLT01.dwg

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025

TABULATION OF QUANTITIES

		DESCRIPTION UNIT L-18 PLAN FINAL PLAN FINAL IT, FURNISH & INSTALL, OPEN TRENCH LF 401 LF 401 SYPLICE BOX, F&I, 113" x 24" COVER SIZE EA 7 ING CONDUCTORS, F&I, INSULATED, NO.8 - 6 LF ING CONDUCTORS, F&I, INSULATED, NO.4 - 2 EA 1614 TOTAL THIS SHEET NUMBERS FINAL PLAN FINAL A01 FINAL 105 FINAL 106 FINAL 107 FINAL 107 FINAL 108 FINAL 109 FINAL 101 FINAL F			440									
PAY ITEM	DESCRIPTION		L -	L-18								IS	GRANI TOTAI	
NO.			PLAN	FINAL							PLAN	FINAL	PLAN	FINAL
630-2-11	CONDUIT, FURNISH & INSTALL, OPEN TRENCH	LF	401								401		4043	
630 - 2 - 12	CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE	LF											223	
635 - 2 - 11	PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE	EA	7								7		64	
715-1-12	LIGHTING CONDUCTORS, F&I, INSULATED, NO.8 - 6	LF											6717	
715-1-13	LIGHTING CONDUCTORS, F&I, INSULATED, NO.4 - 2	EA	1614								1614		14988	
715-516-110	LIGHT POLE COMPLETE, DIRECT BURIED, F&I, POLE TOP MOUNT, 10'	EA	7								7		65	

	REVISIONS		
DATE	DESCRIPTION		
		Lochner	

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



TABULATION OF QUANTITIES

SHEET NO. L-3

RECEIVED: 05/06/2025

- 2. THE ELECTRICAL CONTRACTOR TO PROVIDE ALL MATERIALS AND LABOR TO INSTALL THE ELECTRICAL SYSTEMS AS INDICATED ON THE DRAWINGS. IT IS NOT THE INTENT OF THESE PLANS TO SHOW EVERY MINOR DETAIL OF CONSTRUCTION. ITEMS NOT SHOWN BUT OBVIOUSLY NECESSARY FOR COMPLETION OF THE WORK SHALL BE INCLUDED.
- 3. THE INSTALLATION SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, NFPA-70, 2020, FLORIDA BUILDING CODE, EIGHTH EDITION 2023, NFPA-101 2021, LOCAL CODES, AND OTHER APPLICABLE JURISDICTION CODES.
- 4. THE CONTRACTOR TO OBTAIN ALL NECESSARY PERMITS, INSPECTIONS, AND APPROVALS. ALL WORK SHALL BE DONE BY A LICENSED FLECTRICIAN.
- 5. THE CONTRACTOR TO COORDINATE THE WORK WITH THE ENGINEER AND OWNER.
- 6 THE CONTRACTOR SHALL DETERMINE THE SERVICE REQUIRED DATE FOR THE POWER COMPANY CONFERENCE

CONTRACTOR TO FURNISH AND INSTALL THE ELECTRICAL SYSTEM AS DEPICTED ON ELECTRICAL DRAWINGS.

- GROUNDING TO BE INSTALLED TO MEET NEC. ARTICLE 250 REQUIREMENTS. A GROUNDING SYSTEM SHALL NOT EXCEED A 48-HOUR DRY RESISTANCE OF 10 OHMS. ADDITIONAL GROUNDING TO MEET THIS REQUIREMENT SHALL BE INSTALLED AT NO EXTRA COST. GROUNDING AND BONDING CONNECTIONS SHALL NOT BE PAINTED. TESTING SHALL BE PERFORMED IN THE PRESENCE OF THE ENGINEER. AN EQUIPMENT GROUND WIRE SIZED PER NEC SHALL BE PULLED IN ALL ELECTRICAL CONDUITS.
- 8. ALL EQUIPMENT AND MATERIALS SHALL BE NEW, FURNISHED, AND UL LISTED
- 9. UNDERGROUND CONDUITS SHALL BE SCHEDULE 40 PVC. ALL ABOVE GRADE CONDUITS SHALL BE RIGID GALVANIZED STEEL CONDUIT.
- 10. ELECTRICAL WARNING TAPE SHALL BE PLACED 12 INCHES DEEP ON TOP OF ALL UNDERGROUND TRENCHES.
- 11. ALL TRENCHES SHALL BE FILLED WITH COMPACTED EXISTING CLEAN BACKFILL (98% AASHTO T-99) AND COMPACTED UTILIZING COMPACTION MACHINE AT DEPTH OF NOT MORE THAN 6 INCH LAYERS.
- 12. ALL UNDERGROUND ELECTRICAL CONDUITS SHALL BE A MINIMUM OF 24 INCHES DEEP TO TOP OF BRANCH CIRCUIT CONDUIT AND 36 INCHES DEEP TO THE TOP OF FEEDER CONDUIT FROM FPL TRANSFORMER, UNLESS NOTED OTHERWISE.
- 13. INSTALL PULL BOXES AS NECESSARY TO ACCOMMODATE LONG CABLE PULLS. INSTALL DUCT SEALS AT END OF CONDUITS THAT ENTER PULL BOXES, AND JUNCTION BOXES. LEAVE A MINIMUM OF 6 INCH SPACE BETWEEN WIRES AND PULL BOX COVERS.
- 14. THE DRAWINGS ARE NOT INTENDED TO SHOW THE EXACT LOCATION OF CONDUIT RUNS. TRENCHING SHALL BE COORDINATED WITH OTHER TRADES SUCH AS LANDSCAPING, AND OTHER UNDERGROUND UTILITIES SO THAT CONFLICTS ARE AVOIDED PRIOR TO INSTALLATION, ADDITIONALLY, MAINTAIN ENOUGH DISTANCE FROM EXISTING TREES AND LANDSCAPE AREAS SUCH THAT MINIMUM DAMAGE IS DONE TO EXISTING ROOTS.
- 15. THE CONTRACTOR IS RESPONSIBLE TO TEST ALL SYSTEMS AND REPAIR OR REPLACE ALL DEFECTIVE WORK TO THE SATISFACTION OF THE ENGINEER AND OWNER
- 16. TYPE WRITTEN PANEL SCHEDULE SHALL BE INSTALLED IN THE PANEL BOARDS. ALL CIRCUITS SHALL BE IDENTIFIED IN PULL BOXES, PANEL BOARDS AND CONTRACTORS IDENTIFICATION SHALL MATCH PANEL BOARD SCHEDULE
- 17. THE CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH THE EXISTING CONDITIONS AND THE COORDINATION OF THE WORK, ANY OMISSIONS OR CONFLICT IN THE WORKING DRAWINGS OR BETWEEN THE DRAWINGS AND EXISTING FIELD CONDITIONS WHICH MAY INTERFERE WITH THE PROPER EXECUTION AND COMPLETION OF THE DESCRIBED WORK SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH THE WORK.
- 18. TWO WEEKS AFTER JOB COMPLETION, THE CONTRACTOR SHALL PERFORM ONE NIGHT CHECK OF LIGHTS WITH ENGINEER. REPAIR OR REPLACE NON-FUNCTIONING LUMINARIES AND NOTIFY THE CITY.
- 19. CONTRACTOR SHALL TAKE ALL NECESSARY STEPS TO PREVENT OBJECTIONABLE BLOWING OR DRIFTING OF DIRT, SOIL, OR OTHER DEBRIS DURING EXCAVATION AND INSTALLATION OF ELECTRICAL CONDUIT.
- 20. THE CONTRACTOR SHALL LEAVE THE SITE CLEAN AND ORDERLY AT THE END OF EACH WORKDAY
- 21. ALL MATERIALS AND EQUIPMENT SHALL BE STORED AND INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS UNLESS OTHERWISE NOTED.
- 22. CONTRACTOR TO SUBMIT SHOP DRAWINGS & CATALOG NUMBERS FOR ALL NEW MATERIAL FOR APPROVAL BY THE ELECTRICAL CONSULTANT PRIOR TO CONSTRUCTION.
- 23. EVERY ATTEMPT SHALL BE MADE TO PROTECT ALL EQUIPMENT & MATERIAL FROM ANY DAMAGE DURING TRANSPORTATION, LOADING, UNLOADING, AND INSTALLATION AT THE SITE.
- 24. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOST, STOLEN OR DAMAGED EQUIPMENT OR MATERIAL.
- 25. ALL EQUIPMENT INSTALLED OUTSIDE OR EXPOSED TO WEATHER SHALL BE NEMA TYPE 4X UNLESS NOTED OTHERWISE.
- 26. ALL GRASS AREAS AFFECTED BY CONSTRUCTION SHALL BE RE-SODDED TO MATCH THE EXISTING (EX. ZOYSIA. ST. AUGUSTINE).
- 27. THE CONTRACTOR SHALL TAKE SPECIAL NOTE OF SOIL CONDITIONS THROUGHOUT THIS PROJECT. ANY SPECIAL SHORING, SHEETING OR OTHER PROCEDURES NECESSARY TO PROTECT ADJACENT PROPERTY, PUBLIC OR PRIVATE, DURING THE EXCAVATION OF SUBSOIL MATERIAL AND EXFILTRATION TRENCH, OR FILLING OF ANY AREA, OR FOR ANY OPERATION DURING CONSTRUCTION, SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

- 28. THE CONTRACTOR SHALL RESTRICT PERSONNEL, THE USE OF EQUIPMENT, AND THE STORAGE OF MATERIALS LIMITS OF CONSTRUCTION AND DESIGNATED STAGING AREA.
- 29. ALL EXCESS MATERIAL IS TO BE REMOVED AND DISPOSED BY THE CONTRACTOR WITHIN 72 HOURS OF BEING DEPOSITED IN THE CONSTRUCTION PROJECT LIMITS. CONTRACTOR SHALL INCUR ALL COSTS FOR DISPOSAL.
- 30. DISPOSAL OF ALL MATERIALS, RUBBISH, AND DEBRIS SHALL BE MADE AT A LEGAL DISPOSAL SITE OR BY OTHER PRIOR APPROVED MANNER. MATERIAL CLEARED FROM THE SITE AND DEPOSITED ON ADJACENT OR NEARBY PROPERTY WILL NOT BE CONSIDERED AS HAVING BEEN DISPOSED OF SATISFACTORILY.
- 31. WHEN DISSIMILAR MATERIAL CONNECTIONS ARE MADE, SUCH AS CONCRETE TO METAL, THE DISSIMILAR MATERIAL SHALL BE SEPARATED BY COATING THE CONTACT SURFACE WITH BITUMASTIC MATERIAL.
- 32. THE INFORMATION PROVIDED IN THESE DRAWINGS IS SOLELY TO ASSIST THE CONTRACTOR IN ASSESSING THE NATURE AND EXTENT OF CONDITIONS WHICH WILL BE ENCOUNTERED DURING THE COURSE OF WORK, THE CONTRACTORS ARE DIRECTED, PRIOR TO BIDDING TO CONDUCT WHATEVER INVESTIGATIONS THEY DEEM NECESSARY TO ARRIVE AT THEIR OWN CONCLUSIONS REGARDING THE ACTUAL CONDITIONS THAT WILL BE ENCOUNTERED AND UPON WHICH BIDS WILL BE BASED.
- 33. OPERATING INSTRUCTIONS: UPON COMPLETION OF ALL WORK AND OF ALL TESTS, FURNISH THE NECESSARY SKILLED LABOR AND HELPERS, FOR OPERATING ALL ELECTRICAL SYSTEMS AND EQUIPMENT IN ORDER TO INSTRUCT AND TRAIN THE OWNERS' REPRESENTATIVES IN THE OPERATION AND MAINTENANCE OF ALL EQUIPMENT FURNISHED.
- 34. OPERATION AND MAINTENANCE MANUALS: WITHIN 30 DAYS AFTER THE DATE OF SYSTEM ACCEPTANCE, THE CONTRACTOR SHALL PROVIDE TO THE OWNER, OPERATION AND MAINTENANCE MANUALS CONTAINING SUBMITTAL DATA STATING EQUIPMENT RATING, SELECTED OPTIONS AND REQUIRED MAINTENANCE ACTIONS FOR EACH PIECE OF EQUIPMENT REQUIRING MAINTENANCE THE CONTRACTOR SHALL ALSO PROVIDE THE NAME AND ADDRESS OF AT LEAST ONE QUALIFIED SERVICE AGENCY.
- 35. RECORD DRAWINGS: THE CONTRACTOR IS RESPONSIBLE FOR ALL AS-BUILT DRAWINGS, WHICH SHALL BE PROVIDED TO THE OWNER WITHIN 30 DAYS AFTER THE DATE OF SYSTEM ACCEPTANCE. THEY SHALL INCLUDE A ACTUAL CONDUIT RUNS, PULL BOX LOCATIONS, AND ANY AND ALL EQUIPMENT THAT IS PROVIDED AND INSTALLED AS PART OF THIS PROJECT INDICATING AN ACCURATE DEPICTION OF ALL INSTALLED ELECTRICAL EQUIPMENT.
- 36. BRANCH CIRCUIT VOLTAGE DROP: CONTRACTOR TO VERIFY THAT THE VOLTAGE DROP FOR ALL THE BRANCH CIRCUITS DOES NOT EXCEED TO ADJUST FOR THE VOLTAGE 3% OF THE HOMERUN CIRCUITS ORIGINAL VOLTAGE AND TO INCREASE THE WIRE SIZE AS NECESSARY TO ADJUST FOR THE VOLTAGE
- 37. UNGROUNDED CONDUCTORS SHALL USE BLACK INSULATION. NEUTRAL CONDUCTORS SHALL USE WHITE INSULATION, & GROUNDING CONDUCTORS SHALL USE GREEN INSULATION
- 38. ALL EXPOSED OR SURFACE MOUNTED CONDUIT SHALL BE RIGID GALVANIZED STEEL CONDUIT.
- 39. ALL CONDUIT THAT WILL REMAIN EMPTY AS SPARES SHALL BE MANDREL TESTED, CLEANED INSIDE AND BOTH ENDS CAPPED. LEAVE CORROSION RESISTANT, PULL/DRAG WIRE AND PLACE DUCT MARKERS, OR PULLBOXES TO MARK THE LOCATION OF THE ENDS OF THE CONDUIT
- 40. PULL BOXES SHALL BE LOCATED AT ENDS OF CONDUIT CROSSING ROADWAYS, AND AS NECESSARY FOR THE COMPLETION OF THE PROJECT. INSTALL WITH A 12" BED OF PEAROCK OR CRUSHED STONE FOR DRAINAGE
- 41. THESE PLANS REPRESENT MINIMUM ACCEPTABLE CRITERIA. THE INSPECTION PER THESE DRAWINGS REPRESENT THE MINIMUM BASE ACCEPTANCE.
- 42. TRAIL TO REMAIN ACCESSIBLE TO PEDESTRIANS AT ALL TIMES DURING CONSTRUCTION. PROVIDE A MINIMUM OF 4FT OF UNOBSTRUCTED PATH AROUND WORK ZONES. IF 4FT OF UNOBSTRUCTED PATH CANNOT BE MAINTAINED, PROVIDE TEMPORARY PATH AROUND WORKZONE OR PROVIDE PEDESTRIAN DETOURS AS REQUIRED.
- 43. THE FILL MATERIALS WITHIN THE CANAL RIGHT-OF-WAY SHOULD CONSIST OF THE LIMEROCK BASE FILL MATERIAL THAT IS FREE OF CONTAMINANTS AND MEETS THE CLEAN FILL CRITERIA DEFINITION PURSUANT TO CHAPTER 24-5 OF THE CODE OF MIAMI-DADE COUNTY THE LIMEROCK BASE FILL MATERIAL ALSO SHOULD MEET THE REQUIREMENTS OF THE FDOT STANDARD SPECIFICATIONS, DATED FY 2025-26 OR THE CURRENT AVAILABLE STANDARD SPECIFICATIONS AT THE TIME OF CONSTRUCTION, SECTIONS 911-1 THROUGH 911-2.3, AND 911-3.1 THROUGH 911-3.4.

REVISIONS DATE DESCRIPTION

JOSEPH M. CALDERON TORRES II. P.E. P.E. LICENSE NUMBER 90625 HW LOCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



GENERAL NOTES

SHEET

I:\MIA\PRJ\000021994\700 CADD\Lighting\Beacon Trail\GNNTLT01.dwg

SPECIAL NOTES

- 1. THE ELECTRICAL CONTRACTOR SHALL VERIFY ALL UTILITIES BY ELECTRONIC METHODS AND PRE-TRENCHING IN COORDINATION WITH ALL UTILITY COMPANIES, PRIOR TO BEGINNING ANY CONSTRUCTION OPERATIONS.
- 2. THE CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT ALL EXISTING UNDERGROUND AND ABOVE GROUND IMPROVEMENTS SUCH AS CONDUITS, GAS MAINS, SANITARY SEWER LINES, TV CABLE, TELEPHONE, LATERALS, WATER MAINS, POLES, PIPES, CABLES AND OTHER STRUCTURES FROM INJURY, AND IN CASE OF DAMAGE THEY SHALL BE RESTORED WITHOUT COMPENSATION.
- 3. HAND-DIG WHERE THERE IS ANY CONFLICT WITH THE EXISTING UNDERGROUND UTILITIES.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTACT ALL UTILITY COMPANIES FOR LOCATION OF THEIR EXISTING FACILITIES. IT'S THE CONTRACTOR'S RESPONSIBILITY TO LOCATE THESE UTILITIES FOR THE EXACT DEPTH. CONTACT "SUNSHINE"AT 811 PRIOR TO
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL DAMAGES SUSTAINED OR COST INCURRED BECAUSE OF THE CONTRACTOR'S OPERATION IN THE VICINITY OF EXISTING UTILITIES OR STRUCTURES. THE CONTRACTOR SHALL NOTIFY THE APPROPRIATE UTILITY COMPANIES WHEN THEIR EXISTING FACILITIES CONFLICT WITH THE CONSTRUCTION.
- 6. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE TO CONTACT/LOCATE OTHER UTILITIES NOT SUBSCRIBING TO "SUNSHINE".
- 7. CONTRACTOR TO USE CAUTION WHEN WORKING UNDER AND IN THE VICINITY OF OVERHEAD AND UNDERGROUND UTILITIES. PROVIDE A LETTER FROM FPL APPROVING METHOD OF LIGHT POLE INSTALLATION. CONTACT JESSICA SALAZAR AT JESSICA.SALAZAR@FPL.COM PRIOR TO CONSTRUCTION.
- 8. LIGHT POLE USED AS BASIS OF DESIGN IS HAPCO'S ROUND TAPERED ALUMINUM (RTA) POLE, OR APPROVED EQUAL. POLES SHALL BE DIRECT BURIED AS PER MANUFACTURER'S RECOMMENDATION AND DESIGNED FOR A WIND SPEED ACCORDING TO THE 2020 FLORIDA
- 9. CONTRACTOR IS TO REMOVE ALL SHRUBS/BUSHES WITHIN A 4 FT RADIUS OF ALL LIGHT POLE LOCATIONS TO ALLOW ADEQUATE SPACE FOR ACCESS AND MAINTENANCE. TRIM TREE BRANCHES WITHIN 2 FT RADIUS OF ALL LIGHT POLE LOCATIONS. VERIFY OWNERSHIP AND COORDINATE REMOVAL AND TRIMMING OF BUSHES, SHRUBS, AND TREES WITH OWNER. REPLACE ANY REMOVED TREES, BUSHES, AND SHRUBS IN KIND.

GUARANTEE

THE CONTRACTOR SHALL SUBMIT A WRITTEN GUARANTEE COVERING ALL MATERIALS, WORKMANSHIP, AND EQUIPMENT FOR A PERIOD OF ONE (1) YEAR COMMENCING FROM THE DAY OF FINAL ACCEPTANCE. ANY REPAIRS DUE TO DEFECTIVE WORKMANSHIP OR MATERIALS DURING THE ONE-YEAR PERIOD SHALL BE MADE BY THE CONTRACTOR WITHOUT CHARGE TO THE CITY.

REVISIONS DATE DESCRIPTION

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 HW INCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*




GENERAL NOTES


SHEET


Hernandez, Kevin

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025

CITY OF DORAL







DATE DESCRIPTION PLOCHNER

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



TYPICAL SECTIONS

SHEET NO.

L-6

I:\MIA\PRJ\000021994\700_CADD\Lighting\Beacon Trail\GNNTLT02.dwg

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025

LEGEND

DESCRIPTION SYMBOLS

Q

POST TOP LIGHT POLE WITH 54W LED LUMINAIRE DESIGNED FOR 5,983 LUMENS, TYPE IV DISTRIBUTION, 4000K CCT, AND WIRED FOR 240V OPERATION. USE LITHONIA'S RADIAN POST TOP LED WITH CURVE RADPT_LED_P3_40K_PATH_HS. LUMINAIRES TO BE EQUIPPED WITH HOUSE SIDE SHIELDS.



POST TOP LIGHT POLE WITH 86W LED LUMINAIRE DESIGNED FOR 9,209 LUMENS, TYPE IV DISTRIBUTION, 4000K CCT, AND WIRED FOR 240V OPERATION. USE LITHONIA'S RADIAN POST TOP LED WITH CURVE RADPT_LED_P4_40K_PATH_HS. LUMINAIRES TO BE EQUIPPED WITH HOUSE SIDE SHIELDS.



EXISTING POLE LIGHT TO REMAIN



EXISTING SOLAR POWERED LIGHT POLE TO BE REMOVED AND DISPOSED.



EXISTING LIGHT POLE AND FOUNDATION TO BE REMOVED AND DISPOSED.



PROPOSED LOAD CENTER



EXISTING LOAD CENTER



2" SCHEDULE 40 PVC CONDUIT, DIRECT BURIED IN OPEN TRENCH, CONTAINING CIRCUIT CONDUCTORS AS INDICATED ON PLANS. ALL CONDUCTORS SHALL BE STRANDED COPPER WITH THWN-2 INSULATION. GROUND CONDUCTORS SHALL HAVE GREEN COLOR INSULATION. RUN GROUND CONDUCTORS WITH OTHER CONDUCTORS.



2" HDPE CONDUIT INSTALLED BY DIRECTIONAL BORE, CONTAINING CIRCUIT CONDUCTORS AS INDICATED ON PLANS. ALL CONDUCTORS SHALL BE STRANDED COPPER WITH THWN-2 INSULATION. GROUND CONDUCTORS SHALL HAVE GREEN COLOR INSULATION. RUN GROUND CONDUCTORS WITH OTHER CONDUCTORS.



PULL BOX

1. COORDINATE LIGHT POLE AND LUMINAIRE COLORS WITH THE CITY OF DORAL PRIOR TO PROCUREMENT.

	REVISIONS				
DATE	DESCRIPTION				
				chne	
			_		

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 HW INCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



SIDEWALKS AND SHARED USE PATH

LIGHTING CRITERIA (BEACON TRAIL)

2.5 FOOT CANDLES 4:1 OR LESS 10:1 OR LESS

160 MPH

AVERAGE INITIAL INTENSITY UNIFORMITY RATIO AVG./MIN.

UNIFORMITY RATIO MAX./MIN.

WIND SPEED

LE GEND

I:\MIA\PRJ\000021994\700_CADD\Lighting\Beacon Trail\GNNTLT03.dwg

SHEET

Hernandez, Kevin

Public Works Department

Public Works Department
Permit #PWUT-2505-0061
RECEIVED: 05/06/2025

Part				1																		· ©	111111 #P VV U 1-23
Marche M		Easting	Northina	Racolino	Station	Officat	Foundation					Type		Lumons		CCT(K)	1			Center		м RE	CEIVED: 05/0
March Marc											1											Doral	715-516-110
Second Second Methods March March March March March											1												+
March Marc											1												
Fig.											1												+
March Marc	P-5										1												
Company Comp											1												+
Fig.			-						N/A		1												+
PASS PASS MARS	P-8								N/A		1												+
	P-9		-		20+84.75	38.82' LT	DIRECT	N/A	N/A		1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	2	Doral	715-516-110
Fig.	P-10			NW 25TH ST	21+44.75	38.82' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	A	2	Doral	715-516-110
Fig. 1985					22+04.75		DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV		0	86	240V	A	2	Doral	+
Fig. 1985	P-12	859732.257	532451.689	NW 25TH ST	22+64.75	38.82' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	A	2	Doral	715-516-110
Port State											1												+
Post	P-14							N/A	N/A		1		RADPT						240V	A		Doral	
P. C. \$8,000 \$2,000 \$1											1									A			+
P. 17 \$800,00.42 \$30448.22 \$1.0 \$2			-								1									A			+
											1												+
Part			-						1		1												+
P-22 66022-427 53261-882 68 259-57 2469-89 37 6 of 500-000 74 5 of 500-000 74 5 of 500-000 74 5 of 75 5 of 7											1												
P-22 66203-454 \$2225.23 \$											1												+
Post 78											1												+
Part Mark					+						1												+
P-25									-		1												+
P-25 86557.44 532494.651 WA 25TH ST 30468.59 35.52 CT 0.00CCT 9.7 N/A 1.0 1 NOST TOP ROPT 9209 W 4000K 0 86 240W A 2 0.00CT 71.5-516-170 NOST 70.00CT 9209 W 4000K 0 86 240W A 2 0.00CT 71.5-516-170 NOST 70.00CT 9209 W 4000K 0 86 240W A 2 0.00CT 71.5-516-170 NOST 70.00CT 9209 W 4000K 0 86 240W A 2 0.00CT 71.5-516-170 NOST 70.00CT 9209 W 4000K 0 86 240W A 2 0.00CT 71.5-516-170 NOST 70.00CT 9209 W 4000K 0 86 240W A 2 0.00CT 71.5-516-170 NOST 70.00CT 9209 W 4000K 0 86 240W A 2 0.00CT 71.5-516-170 NOST 70.00CT 92.00CT											1												+
P-28 REBESTARE \$23255-889 MF 25T1-5T \$1445.21 \$3.878 LT DIRECT MA			-								1												+
P-77 680689473 532454927 MW 25TH ST 32421.93 3582 LT OMECT M/A M/A 10 1 P35T TOP ABDPT 9209 IV 4000K 0 85 240V A 2 Drial 715516-110 P-29 660021 434 53245502 WW 25TH ST 3325030 3381 T OMECT M/A M/A 10 1 P35T TOP RAPPT 9209 IV 4000K 0 86 240V A 2 Devid 715516-110 P-30 600821 433 532450.29 WW 25TH ST 3441993 3589 LT OMECT M/A M/A 10 1 P59T TOP RAPPT 9209 IV 4000K 0 86 240V A 2 Devid 715-516-110 P-23 8008024-31 532450.29 MW 25TH ST 344993 3589 LT OMECT M/A M/A 10 1 P59T TOP RAPPT 9209 IV 4000K 0 66											1												+
Page 860/35.85 32255.86 MR 25H 51 3248/82 2582 LI DIRECT N/A M/A 10 1 POST TOP RADPT 9209 N/ 4000K 0 86 240V A 2 Doral 715-516-110 715-716-710 715-716											1												+
P-29 868821.334 \$3245.829											1												+
P-30 868687.42 53245.62											1												+
P-31 860953421 53245669 WW 25TH 5T 348593 3580 CT											1									A			
P-32 861019429 52457.146 0W 251H ST 35+51.93 33.89 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 2 DOCAL 715-516-110 P-33 86120.078 532461.374 W 251H ST 37+2.61 39.02 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 2 DOCAL 715-516-110 P-35 861320.078 532461.257 WW 251H ST 38+52.61 39.02 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-36 861320.078 532462.57 WW 251H ST 38+52.61 39.02 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-36 861320.078 532462.699 WW 251H ST 38+52.61 38.92 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-36 861320.078 532462.699 WW 251H ST 38+52.61 38.92 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-37 861640.075 532462.699 WW 251H ST 38+92.61 38.92 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-37 861650.075 532462.699 WW 251H ST 40+62.61 38.92 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-37 861650.075 53246.405 WW 251H ST 41-32.61 38.92 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-37 86164.005 53246.405 WW 251H ST 42-02.61 38.92 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-41 861740.099 53246.409 WW 251H ST 42-02.61 38.82 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-41 861740.099 53246.909 WW 251H ST 42-02.61 38.82 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-42 86180.066 532465.318 WW 251H ST 42-02.61 38.82 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-42 86180.066 532465.318 WW 251H ST 43-42.61 38.82 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 715-516-110 P-44 861950.065 532465.318 WW 251H ST 43-42.61 38.82 (T DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000X 0 86 240V A 3 DOCAL 7											1									A			_
P-33 86180.081 532461.374 WW 25TH ST 37412.61 39.06 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 2 Doral 715-516-110 P-34 861250.079 532461.816 WW 25TH ST 3742.61 39.07 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 2 Doral 715-516-110 P-36 861380.076 532462.699 WW 35TH ST 349-2.61 38.96 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-36 861380.076 532462.699 WW 35TH ST 349-2.61 38.96 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-37 861480.075 532463.14 WW 25TH ST 349-2.61 38.96 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 86150.074 532463.82 WW 25TH ST 349-2.61 38.96 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 86150.074 532463.82 WW 25TH ST 349-2.61 38.96 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 86160.077 532463.03 WW 25TH ST 349-2.61 38.96 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-39 86160.077 532463.405 WW 25TH ST 414-3.61 38.91 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-40 861670.071 532463.405 WW 25TH ST 414-3.61 38.91 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-40 861670.071 532463.405 WW 25TH ST 424-2.61 38.89 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-40 86180.066 532465.348 WW 25TH ST 444-2.61 38.81 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-40 86180.066 532465.348 WW 25TH ST 444-2.61 38.81 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-44 86180.066 532465.348 WW 25TH ST 444-2.61 38.81 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-44 86180.066 532465.356 WW 25TH ST 444-2.61 38.81 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 71											1									A			+
P-34 861250.079 532461.816 NW 25TH ST 37+82.61 39.07 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 2 Doral 715-516-110 P-35 861320.078 532462.257 NW 25TH ST 38+32.61 39.07 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-37 861480.075 532462.699 NW 25TH ST 39+32.61 38.98° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 861530.074 532463.582 NW 25TH ST 39+32.61 38.98° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 86150.071 532463.032 NW 25TH ST 41+32.61 38.94° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-39 861600.072 532463.033 NW 25TH ST 41+32.61 38.94° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-30 861600.072 532464.033 NW 25TH ST 41+32.61 38.94° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-30 861600.072 532464.033 NW 25TH ST 41+32.61 38.89° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-41 861740.069 532464.053 NW 25TH ST 41+32.61 38.89° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-42 861810.068 532465.348 NW 25TH ST 43+42.61 38.89° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-43 861880.067 532465.789 NW 25TH ST 44+2.61 38.89° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-44 861950.065 532465.789 NW 25TH ST 44+2.61 38.89° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-48 86200.064 532466.673 NW 25TH ST 44+2.61 38.89° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-48 86200.066 532466.714 NW 25TH ST 44+2.61 38.70° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-48 86200.066 532466.714 NW 25TH ST 44+2.61 38.70° LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86	P-33			NW 25TH ST	37+12.61		DIRECT	N/A	N/A		1	POST TOP	RADPT	9209			0	86	240V	A	2	Doral	+
P-35 861320.078 532462.257 NW 25TH ST 38±52.61 39.0" LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-36 861390.076 532462.699 NW 25TH ST 39±2.61 38.98 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 86159.0074 532463.14 NW 25TH ST 39±2.61 38.98 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 86159.0074 532463.14 NW 25TH ST 40±62.61 38.98 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 86150.0074 532463.02 NW 25TH ST 40±62.61 38.98 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 861670.071 532464.023 NW 25TH ST 42±02.61 38.98 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-410 861670.0071 532464.056 NW 25TH ST 42±02.61 38.88 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-410 861740.069 532465.348 NW 25TH ST 42±02.61 38.88 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-42 861810.068 532465.348 NW 25TH ST 42±02.61 38.88 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-42 861810.068 532465.789 NW 25TH ST 42±02.61 38.88 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-43 86180.067 532465.789 NW 25TH ST 42±0.61 38.81 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 86180.067 532465.789 NW 25TH ST 44±0.61 38.72 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862020.064 532465.789 NW 25TH ST 44±0.61 38.72 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862020.064 532465.789 NW 25TH ST 44±0.61 38.72 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862020.064 532465.789 NW 25TH ST 44±0.61 38.72 LT DIRECT N/A N/A 10° I POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Dor								N/A	N/A		1		RADPT						240V	A	2	Doral	+
P-36 861390.076 532462.699 NW 25TH ST 39+22.61 38.98 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.37 86146.075 532463.14 NW 25TH ST 39+22.61 38.98 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.38 861530.074 532463.582 NW 25TH ST 40+62.61 38.94 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.39 861600.072 532464.023 NW 25TH ST 42+02.61 38.89 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.40 861670.071 532464.055 NW 25TH ST 42+02.61 38.89 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.41 861740.069 532464.906 NW 25TH ST 42+02.61 38.89 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.42 861810.068 532465.348 NW 25TH ST 43+42.61 38.84 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.43 86180.066 532465.348 NW 25TH ST 43+42.61 38.84 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.43 86180.066 532465.789 NW 25TH ST 43+42.61 38.84 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.43 86180.066 532465.789 NW 25TH ST 43+42.61 38.87 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.43 86180.066 532465.789 NW 25TH ST 43+42.61 38.87 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.45 862020.064 532466.673 NW 25TH ST 45+52.61 38.77 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.45 862020.064 532466.673 NW 25TH ST 45+52.61 38.74 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.46 862090.063 532467.114 NW 25TH ST 45+52.61 38.74 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P.46 862090.063 532467.114 NW 25TH ST 46+22.61 38.74 LT DIRECT N/A N/A 10 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-1											1									A	3		+
P-37 861460.075 532463.14 NW 25TH ST 39+92.61 38.96 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-38 861530.074 532463.582 NW 25TH ST 40+62.61 38.94 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-39 861600.072 532464.023 NW 25TH ST 41+32.61 38.91 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-40 861670.071 532464.465 NW 25TH ST 42+02.61 38.91 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-42 861810.068 532465.348 NW 25TH ST 42+02.61 38.81 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-43 86180.067 532465.789 NW 25TH ST 44+12.61 38.81 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-44 861950.065 532466.231 NW 25TH ST 44+12.61 38.79 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862020.064 532466.73 NW 25TH ST 45+52.61 38.79 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862090.063 532466.73 NW 25TH ST 45+52.61 38.79 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862090.063 532466.73 NW 25TH ST 45+52.61 38.79 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.516 NW 25TH ST 45+52.61 38.72 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.516 NW 25TH ST 46+92.61 38.72 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.516 NW 25TH ST 46+92.61 38.72 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.516 NW 25TH ST 46+92.61 38.72 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.516 NW 25TH ST 46+92.61 38.72 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3			-								1									A			+
P-38 861530.074 532463.582 NW 25TH ST 40+62.61 38.94 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-39 861600.072 532464.023 NW 25TH ST 41+32.61 38.91' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-40 861670.071 532464.495 NW 25TH ST 42+02.61 38.89' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-41 861740.069 532464.936 NW 25TH ST 42+72.61 38.89' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>N/A</td><td></td><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>									N/A		1												
P-39 861600.072 532464.023 NW 25TH ST 41+32.61 38.91' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-40 861670.071 532464.465 NW 25TH ST 42+02.61 38.89' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-41 86174.0069 532464.906 NW 25TH ST 42+72.61 38.86' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-42 861810.068 532465.348 NW 25TH ST 43+42.61 38.81' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K <											1												+
P-40 861670.071 532464.465 NW 25TH ST 42+02.61 38.89 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 400K 0 86 240V A 3 Doral 715-516-110 P-41 861740.069 532464.966 NW 25TH ST 42+72.61 38.86' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-42 861810.068 532465.348 NW 25TH ST 43+42.61 38.81' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-43 86180.067 532465.348 NW 25TH ST 44+12.61 38.81' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K	P-39			NW 25TH ST		38.91' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V		3	Doral	+
P-41 861740.069 532464.906 NW 25TH ST 42+72.61 38.86 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-42 861810.068 532465.348 NW 25TH ST 43+42.61 38.84 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-43 861880.067 532465.789 NW 25TH ST 44+12.61 38.81' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-44 861950.065 532466.231 NW 25TH ST 44+82.61 38.71' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45<	P-40		532464.465		42+02.61	38.89' LT	DIRECT	N/A	N/A		1	POST TOP	RADPT	9209	IV	4000K	0		240V	A	3	Doral	715-516-110
P-42 861810.068 532465.348 NW 25TH ST 43+42.61 38.84 LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-43 861880.067 532465.789 NW 25TH ST 44+12.61 38.81' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-44 861950.065 532466.231 NW 25TH ST 44+82.61 38.79' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862020.064 532466.673 NW 25TH ST 45+52.61 38.74' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46									N/A		1		RADPT										+
P-43 861880.067 532465.789 NW 25TH ST 44+12.61 38.81' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-44 861950.065 532466.231 NW 25TH ST 44+82.61 38.79' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862020.064 532466.673 NW 25TH ST 45+52.61 38.77' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.114 NW 25TH ST 46+22.61 38.72' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K <								N/A	N/A		1	POST TOP	RADPT				0		240V	A			+
P-44 861950.065 532466.231 NW 25TH ST 44+82.61 38.79' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-45 862020.064 532466.673 NW 25TH ST 45+52.61 38.77' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.114 NW 25TH ST 46+22.61 38.74' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-47 862160.061 532467.556 NW 25TH ST 46+92.61 38.72' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K <									N/A		1		RADPT										+
P-45 862020.064 532466.673 NW 25TH ST 45+52.61 38.77' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-46 862090.063 532467.114 NW 25TH ST 46+22.61 38.74' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-47 862160.061 532467.556 NW 25TH ST 46+92.61 38.72' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-48 862230.06 532467.997 NW 25TH ST 47+62.61 38.69' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>											1												
P-46 862090.063 532467.114 NW 25TH ST 46+22.61 38.74' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-47 862160.061 532467.556 NW 25TH ST 46+92.61 38.72' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-48 862300.06 532467.997 NW 25TH ST 47+62.61 38.69' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-49 862300.058 532468.439 NW 25TH ST 48+32.61 38.67' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K <t< td=""><td>P-45</td><td></td><td>-</td><td>NW 25TH ST</td><td></td><td></td><td></td><td></td><td></td><td></td><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>715-516-110</td></t<>	P-45		-	NW 25TH ST							1												715-516-110
P-47 862160.061 532467.556 NW 25TH ST 46+92.61 38.72' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-48 862230.06 532467.997 NW 25TH ST 47+62.61 38.69' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-49 862300.058 532468.439 NW 25TH ST 48+32.61 38.67' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110											1												+
P-48 862230.06 532467.997 NW 25TH ST 47+62.61 38.69' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110 P-49 862300.058 532468.439 NW 25TH ST 48+32.61 38.67' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110											1												+
P-49 862300.058 532468.439 NW 25TH ST 48+32.61 38.67' LT DIRECT N/A N/A 10' 1 POST TOP RADPT 9209 IV 4000K 0 86 240V A 3 Doral 715-516-110																							
											1												
					1					1	-										-		1

Lighting Data Table

	REVISIONS
DATE	DESCRIPTION



JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



POLE DATA

SHEET NO.

na Data Tabla

	Lighting Data Table														Pe	rmit #PWUT-2505-0061						
Pole No.	Easting	Northing	Baseline	Station	Offset	Foundation	Arm Length	Arm Rise	Mount Height	Quantity Luminaires	Type	Make∖ Model	Lumens	IES Dist Type	CCT(K)	Tilt (deg)	Luminaire Watts	Luminaire Volts	Load Center No.	Circuit No.		CEIVED: 05/06/2025
P-51	862440.056	532469.322	NW 25TH ST	49+72.61	38.62' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	A	3	Doral	715-516-110
P-52	862510.054	532469.763	NW 25TH ST	50+42.61	38.60' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	А	3	Doral	715-516-110
P-53	862580.053	532470.205	NW 25TH ST	51+12.61	38.57' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	А	3	Doral	715-516-110
P-54	862650.051	532470.655	NW 25TH ST	51+82.61	38.56' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	А	3	Doral	715-516-110
P-55	862720.05	532471.161	NW 25TH ST	52+52.61	38.60' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	А	3	Doral	715-516-110
P-56	862790.048	532471.668	NW 25TH ST	53+22.61	38.64' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	Α	3	Doral	715-516-110
P-57	862860.046	532472.174	NW 25TH ST	53+92.61	38.68' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	Α	3	Doral	715-516-110
P-58	862930.044	532472.681	NW 25TH ST	54+62.61	38.72' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	Α	3	Doral	715-516-110
P-59	863005.042	532473.187	NW 25TH ST	55+37.61	38.73' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	Α	3	Doral	715-516-110
P-60	863077.54	532473.693	NW 25TH ST	56+10.11	38.75' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	Α	3	Doral	715-516-110
P-61	863152.539	532474.2	NW 25TH ST	56+85.11	38.76' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	Α	3	Doral	715-516-110
P-62	863222.28	532472.498	NW 25TH ST	57+54.84	36.59' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	3	Doral	715-516-110
P-63	863285.164	532473.608	NW 25TH ST	58+17.73	37.29' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	3	Doral	715-516-110
P-64	863350.033	532475.719	NW 25TH ST	58+82.61	38.96' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	3	Doral	715-516-110
P-65	863392.664	532476.108	NW 25TH ST	59+25.24	39.07' LT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	Α	3	Doral	715-516-110

DATE DESCRIPTION

P Lochner

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



POLE DATA

SHEET NO.

L-9

I:\MIA\PRJ\000021994\700_CADD\Lighting\Beacon Trail\PLDTLT01.dwg


Hernandez, Kevin

4/8/2025 9:53:54

CITY OF DORAL
Public Works Department

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025





R E V I S I O N S

DATE DESCRIPTION

4 Lochner


JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178


CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS





PROJECT LAYOUT


SHEET NO. L-10























BOND LIGHT POLE METAL TO GROUND -CONDUCTORS, FOR SPLICE (GELCAP) -SIZE AND QUANTITY SEE EXOTHERMIC — PLANS CONNECTION 13" X 24" X 12" -PULL BOX 12" BED OF -PEAROCK OR CRUSHED STONE FOR DRAINAGE STRAIN RELIEF FITTINGS 5" DIA. X 20' LONG GROUND ROD PULL BOX DETAIL

LIGHT POLE DETAIL

REVISIONS	
DATE DESCRIPTION	
	Lochner

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



LIGHT POLE DETAIL

SHEET NO.	
L-19	

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025


INDEX OF LIGHTING PLANS


SHEET NO.	SHEET DESCRIPTION
L-1	KEYSHEET
L-2	TABULATION OF QUANTITIES
L-3 - L-4	GENERAL NOTES
L-5	TYPICAL SECTIONS
L-6	LEGEND
L-7	POLE DATA
L-8	PROJECT LAYOUT
L-9 - L-15	LIGHTING PLAN
L-16	LIGHT POLE DETAIL

CITY OF DORAL, FLORIDA

TRAIL LIGHTING IMPROVEMENT PLANS

DRESSEL'S DAIRY TRAIL ALONG NW 58TH ST FROM NW 117TH AVE TO NW 114TH AVE





THIS ITEM HAS BEEN DIGITALLY SIGNED AND SEALED BY

Joseph M Calderon Torres 2025.04.08 14:54:06-04'00'

ON THE DATE ADJACENT TO THE SEAL

PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES

LIGHTING PLANS ENGINEER OF RECORD:

JOSEPH M. CALDERON TORRES II, P.E. P.E. NO.: 90625 H.W. LOCHNER, INC 8750 N.W. 36TH STREET, SUITE 360 MIAMI, FLORIDA 33178 TEL: (305) 503-9873; FAX: (305) 503-9882 VENDOR NO.: VF-362-338-11

PERMIT SUBMITTAL

SHEET NO.

L-1

GOVERNING STANDARD PLANS: Florida Department of Transportation, FY2025-26 Standard plans for Road and Bridge Construction and applicable Interim Revisions (Irs).

Standard Plans for Road Construction and associated Irs are available at the following website:

http://www.fdot.gov/design/Standardplans.shtm

APPLICABLE IRs: N/A

Standard Plans for Bridge Construction are included in the Structures Plans Component.

GOVERNING STANDARD SPECIFICATIONS: Florida Department of Transportation, FY 2025-26 Standard Specifications for Road and Bridge Construction at the following website: http://www.fdot.gov/programmanagement/Implemented/SpecBooks

TABULATION OF QUANTITIES									Public Wo	orks Depa WUT-2505	rtment 5-0061						
SHEET NUMBERS TOT														RECEIVE	D: 05/06/2	2025	
ITEM NO.	DESCRIPTION	UNIT	L	- 9	L - 10	L - 11	L-12	L-	13	L-	14	L - 1	15	THIS SHEE	> _T	OTAL	
'\\\'			PLAN	FINAL	PLAN FINAL	PLAN FINAL	PLAN FINAL	PLAN	FINAL	PLAN	FINAL	PLAN	FINAL	PLAN F	INAL PLAI	FINAL	1
630 - 2 - 11	CONDUIT, FURNISH & INSTALL, OPEN TRENCH	LF	452		573	125								1150	1150		
635-2-11	PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE	EA	9		11	3								23	23		-
715-1-12	LIGHTING CONDUCTORS, F&I, INSULATED, NO.8 - 6	LF	2004		2511	341								4856	4856		-
715-1-13	LIGHTING CONDUCTORS, F&I, INSULATED, NO.4 - 2	LF					940	1508		1520		908		4876	4876		
715-516-110	LIGHT POLE COMPLETE, DIRECT BURIED, F&I, POLE TOP MOUNT, 10'	EA	9		11	3								23	23		-
																	-
																	1
<u> </u>																+	f.C.

	REVISIONS	
DATE	DESCRIPTION	
		Lochnor

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



TABULATION OF QUANTITIES

SHEET NO.

Hernandez, Kevin

I:\MIA\PRJ\000021994\700_CADD\Lighting\Dressels Dairy Trail\TABQLT01.dwg

CITY OF DORAL

- . CONTRACTOR TO FURNISH AND INSTALL THE ELECTRICAL SYSTEM AS DEPICTED ON ELECTRICAL DRAWINGS.
- 2. THE ELECTRICAL CONTRACTOR TO PROVIDE ALL MATERIALS AND LABOR TO INSTALL THE ELECTRICAL SYSTEMS AS INDICATED ON THE DRAWINGS. IT IS NOT THE INTENT OF THESE PLANS TO SHOW EVERY MINOR DETAIL OF CONSTRUCTION. ITEMS NOT SHOWN BUT OBVIOUSLY NECESSARY FOR COMPLETION OF THE WORK SHALL BE INCLUDED.
- 3. THE INSTALLATION SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, NFPA-70, 2020, FLORIDA BUILDING CODE, EIGHTH EDITION 2023, NFPA-101 2021, LOCAL CODES, AND OTHER APPLICABLE JURISDICTION CODES.
- 4. THE CONTRACTOR TO OBTAIN ALL NECESSARY PERMITS, INSPECTIONS, AND APPROVALS. ALL WORK SHALL BE DONE BY A LICENSED ELECTRICIAN.
- 5. THE CONTRACTOR TO COORDINATE THE WORK WITH THE ENGINEER AND OWNER.
- 6. THE CONTRACTOR SHALL DETERMINE THE SERVICE REQUIRED DATE FOR THE POWER COMPANY CONFERENCE.
- 7. GROUNDING TO BE INSTALLED TO MEET NEC. ARTICLE 250 REQUIREMENTS. A GROUNDING SYSTEM SHALL NOT EXCEED A 48-HOUR DRY RESISTANCE OF 10 OHMS. ADDITIONAL GROUNDING TO MEET THIS REQUIREMENT SHALL BE INSTALLED AT NO EXTRA COST. GROUNDING AND BONDING CONNECTIONS SHALL NOT BE PAINTED. TESTING SHALL BE PERFORMED IN THE PRESENCE OF THE ENGINEER. AN EQUIPMENT GROUND WIRE SIZED PER NEC SHALL BE PULLED IN ALL ELECTRICAL CONDUITS.
- 8. ALL EQUIPMENT AND MATERIALS SHALL BE NEW, FURNISHED, AND UL LISTED
- 9. UNDERGROUND CONDUITS SHALL BE SCHEDULE 40 PVC. ALL ABOVE GRADE CONDUITS SHALL BE RIGID GALVANIZED STEEL CONDUIT.
- 10. ELECTRICAL WARNING TAPE SHALL BE PLACED 12 INCHES DEEP ON TOP OF ALL UNDERGROUND TRENCHES.
- 11. ALL TRENCHES SHALL BE FILLED WITH COMPACTED EXISTING CLEAN BACKFILL (98% AASHTO T-99) AND COMPACTED UTILIZING COMPACTION MACHINE AT DEPTH OF NOT MORE THAN 6 INCH LAYERS.
- 12. ALL UNDERGROUND ELECTRICAL CONDUITS SHALL BE A MINIMUM OF 24 INCHES DEEP TO TOP OF BRANCH CIRCUIT CONDUIT AND 36 INCHES DEEP TO THE TOP OF FEEDER CONDUIT FROM FPL TRANSFORMER, UNLESS NOTED OTHERWISE.
- 13. INSTALL PULL BOXES AS NECESSARY TO ACCOMMODATE LONG CABLE PULLS. INSTALL DUCT SEALS AT END OF CONDUITS THAT ENTER PULL BOXES, AND JUNCTION BOXES. LEAVE A MINIMUM OF 6 INCH SPACE BETWEEN WIRES AND PULL BOX COVERS.
- 14. THE DRAWINGS ARE NOT INTENDED TO SHOW THE EXACT LOCATION OF CONDUIT RUNS. TRENCHING SHALL BE COORDINATED WITH OTHER TRADES SUCH AS LANDSCAPING, AND OTHER UNDERGROUND UTILITIES SO THAT CONFLICTS ARE AVOIDED PRIOR TO INSTALLATION. ADDITIONALLY, MAINTAIN ENOUGH DISTANCE FROM EXISTING TREES AND LANDSCAPE AREAS SUCH THAT MINIMUM DAMAGE IS DONE TO EXISTING ROOTS.
- 15. THE CONTRACTOR IS RESPONSIBLE TO TEST ALL SYSTEMS AND REPAIR OR REPLACE ALL DEFECTIVE WORK TO THE SATISFACTION OF THE ENGINEER AND OWNER.
- 16. TYPE WRITTEN PANEL SCHEDULE SHALL BE INSTALLED IN THE PANEL BOARDS. ALL CIRCUITS SHALL BE IDENTIFIED IN PULL BOXES,
 PANEL BOARDS AND CONTRACTORS IDENTIFICATION SHALL MATCH PANEL BOARD SCHEDULE
- 17. THE CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH THE EXISTING CONDITIONS AND THE COORDINATION OF THE WORK, ANY OMISSIONS OR CONFLICT IN THE WORKING DRAWINGS OR BETWEEN THE DRAWINGS AND EXISTING FIELD CONDITIONS WHICH MAY INTERFERE WITH THE PROPER EXECUTION AND COMPLETION OF THE DESCRIBED WORK SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO PROCEEDING WITH THE WORK.
- 18. TWO WEEKS AFTER JOB COMPLETION, THE CONTRACTOR SHALL PERFORM ONE NIGHT CHECK OF LIGHTS WITH ENGINEER. REPAIR OR REPLACE NON-FUNCTIONING LUMINARIES AND NOTIFY THE CITY.
- 19. CONTRACTOR SHALL TAKE ALL NECESSARY STEPS TO PREVENT OBJECTIONABLE BLOWING OR DRIFTING OF DIRT, SOIL, OR OTHER DEBRIS DURING EXCAVATION AND INSTALLATION OF ELECTRICAL CONDUIT.
- 20. THE CONTRACTOR SHALL LEAVE THE SITE CLEAN AND ORDERLY AT THE END OF EACH WORKDAY
- 21. ALL MATERIALS AND EQUIPMENT SHALL BE STORED AND INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS UNLESS OTHERWISE NOTED.
- 22. CONTRACTOR TO SUBMIT SHOP DRAWINGS & CATALOG NUMBERS FOR ALL NEW MATERIAL FOR APPROVAL BY THE ELECTRICAL CONSULTANT PRIOR TO CONSTRUCTION.
- 23. EVERY ATTEMPT SHALL BE MADE TO PROTECT ALL EQUIPMENT & MATERIAL FROM ANY DAMAGE DURING TRANSPORTATION, LOADING, UNLOADING, AND INSTALLATION AT THE SITE.
- 24. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOST, STOLEN OR DAMAGED EQUIPMENT OR MATERIAL.

REVISIONS

DESCRIPTION

DATE

- 25. ALL EQUIPMENT INSTALLED OUTSIDE OR EXPOSED TO WEATHER SHALL BE NEMA TYPE 4X UNLESS NOTED OTHERWISE.
- 26. ALL GRASS AREAS AFFECTED BY CONSTRUCTION SHALL BE RE-SODDED TO MATCH THE EXISTING (EX. ZOYSIA, ST. AUGUSTINE).
- 27. THE CONTRACTOR SHALL TAKE SPECIAL NOTE OF SOIL CONDITIONS THROUGHOUT THIS PROJECT. ANY SPECIAL SHORING, SHEETING OR OTHER PROCEDURES NECESSARY TO PROTECT ADJACENT PROPERTY, PUBLIC OR PRIVATE, DURING THE EXCAVATION OF SUBSOIL MATERIAL AND EXFILTRATION TRENCH, OR FILLING OF ANY AREA, OR FOR ANY OPERATION DURING CONSTRUCTION, SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

- 28. THE CONTRACTOR SHALL RESTRICT PERSONNEL, THE USE OF EQUIPMENT, AND THE STORAGE OF MATERIALS RECEIVED: 05/06/2025 LIMITS OF CONSTRUCTION AND DESIGNATED STAGING AREA.
- 29. ALL EXCESS MATERIAL IS TO BE REMOVED AND DISPOSED BY THE CONTRACTOR WITHIN 72 HOURS OF BEING DEPOSITED IN THE CONSTRUCTION PROJECT LIMITS. CONTRACTOR SHALL INCUR ALL COSTS FOR DISPOSAL.
- 30. DISPOSAL OF ALL MATERIALS, RUBBISH, AND DEBRIS SHALL BE MADE AT A LEGAL DISPOSAL SITE OR BY OTHER PRIOR APPROVED MANNER. MATERIAL CLEARED FROM THE SITE AND DEPOSITED ON ADJACENT OR NEARBY PROPERTY WILL NOT BE CONSIDERED AS HAVING BEEN DISPOSED OF SATISFACTORILY.
- 31. WHEN DISSIMILAR MATERIAL CONNECTIONS ARE MADE, SUCH AS CONCRETE TO METAL, THE DISSIMILAR MATERIAL SHALL BE SEPARATED BY COATING THE CONTACT SURFACE WITH BITUMASTIC MATERIAL.
- 32. THE INFORMATION PROVIDED IN THESE DRAWINGS IS SOLELY TO ASSIST THE CONTRACTOR IN ASSESSING THE NATURE AND EXTENT OF CONDITIONS WHICH WILL BE ENCOUNTERED DURING THE COURSE OF WORK. THE CONTRACTORS ARE DIRECTED, PRIOR TO BIDDING, TO CONDUCT WHATEVER INVESTIGATIONS THEY DEEM NECESSARY TO ARRIVE AT THEIR OWN CONCLUSIONS REGARDING THE ACTUAL CONDITIONS THAT WILL BE ENCOUNTERED AND UPON WHICH BIDS WILL BE BASED.
- 33. OPERATING INSTRUCTIONS: UPON COMPLETION OF ALL WORK AND OF ALL TESTS, FURNISH THE NECESSARY SKILLED LABOR AND HELPERS, FOR OPERATING ALL ELECTRICAL SYSTEMS AND EQUIPMENT IN ORDER TO INSTRUCT AND TRAIN THE OWNERS' REPRESENTATIVES IN THE OPERATION AND MAINTENANCE OF ALL EQUIPMENT FURNISHED.
- 34. OPERATION AND MAINTENANCE MANUALS: WITHIN 30 DAYS AFTER THE DATE OF SYSTEM ACCEPTANCE, THE CONTRACTOR SHALL PROVIDE TO THE OWNER, OPERATION AND MAINTENANCE MANUALS CONTAINING SUBMITTAL DATA STATING EQUIPMENT RATING, SELECTED OPTIONS AND REQUIRED MAINTENANCE ACTIONS FOR EACH PIECE OF EQUIPMENT REQUIRING MAINTENANCE THE CONTRACTOR SHALL ALSO PROVIDE THE NAME AND ADDRESS OF AT LEAST ONE QUALIFIED SERVICE AGENCY.
- 35. RECORD DRAWINGS: THE CONTRACTOR IS RESPONSIBLE FOR ALL AS-BUILT DRAWINGS, WHICH SHALL BE PROVIDED TO THE OWNER WITHIN 30 DAYS AFTER THE DATE OF SYSTEM ACCEPTANCE. THEY SHALL INCLUDE A ACTUAL CONDUIT RUNS, PULL BOX LOCATIONS, AND ANY AND ALL EQUIPMENT THAT IS PROVIDED AND INSTALLED AS PART OF THIS PROJECT INDICATING AN ACCURATE DEPICTION OF ALL INSTALLED ELECTRICAL EQUIPMENT.
- 36. BRANCH CIRCUIT VOLTAGE DROP: CONTRACTOR TO VERIFY THAT THE VOLTAGE DROP FOR ALL THE BRANCH CIRCUITS DOES NOT EXCEED 3% OF THE HOMERUN CIRCUITS ORIGINAL VOLTAGE AND TO INCREASE THE WIRE SIZE AS NECESSARY TO ADJUST FOR THE VOLTAGE DROP.
- 37. UNGROUNDED CONDUCTORS SHALL USE BLACK INSULATION, NEUTRAL CONDUCTORS SHALL USE WHITE INSULATION, & GROUNDING CONDUCTORS SHALL USE GREEN INSULATION.
- 38. ALL EXPOSED OR SURFACE MOUNTED CONDUIT SHALL BE RIGID GALVANIZED STEEL CONDUIT.
- 39. ALL CONDUIT THAT WILL REMAIN EMPTY AS SPARES SHALL BE MANDREL TESTED, CLEANED INSIDE AND BOTH ENDS CAPPED. LEAVE CORROSION RESISTANT, PULL/DRAG WIRE AND PLACE DUCT MARKERS, OR PULLBOXES TO MARK THE LOCATION OF THE ENDS OF THE CONDUIT.
- 40. PULL BOXES SHALL BE LOCATED AT ENDS OF CONDUIT CROSSING ROADWAYS, AND AS NECESSARY FOR THE COMPLETION OF THE PROJECT. INSTALL WITH A 12" BED OF PEAROCK OR CRUSHED STONE FOR DRAINAGE.
- 41. THESE PLANS REPRESENT MINIMUM ACCEPTABLE CRITERIA. THE INSPECTION PER THESE DRAWINGS REPRESENT THE MINIMUM BASE ACCEPTANCE.
- 42. TRAIL TO REMAIN ACCESSIBLE TO PEDESTRIANS AT ALL TIMES DURING CONSTRUCTION. PROVIDE A MINIMUM OF 4FT OF UNOBSTRUCTED PATH AROUND WORK ZONES. IF 4FT OF UNOBSTRUCTED PATH CANNOT BE MAINTAINED, PROVIDE TEMPORARY PATH AROUND WORKZONE OR PROVIDE PEDESTRIAN DETOURS AS REQUIRED.
- 43. THE FILL MATERIALS WITHIN THE CANAL RIGHT-OF-WAY SHOULD CONSIST OF THE LIMEROCK BASE FILL MATERIAL THAT IS FREE OF CONTAMINANTS AND MEETS THE CLEAN FILL CRITERIA DEFINITION PURSUANT TO CHAPTER 24-5 OF THE CODE OF MIAMI-DADE COUNTY THE LIMEROCK BASE FILL MATERIAL ALSO SHOULD MEET THE REQUIREMENTS OF THE FDOT STANDARD SPECIFICATIONS, DATED FY 2025-26 OR THE CURRENT AVAILABLE STANDARD SPECIFICATIONS AT THE TIME OF CONSTRUCTION, SECTIONS 911-1 THROUGH 911-2.3, AND 911-3.1 THROUGH 911-3.4.

4 Lochner

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS

JOSEPH M. CALDERON TORRES II. P.E.

CONSULTING ENGINEERS AND PLANNERS

8750 NW 36th STREET - SUITE 360

P.E. LICENSE NUMBER 90625

MIAMI, FLORIDA - 33178

HW LOCHNER INC



GENERAL NOTES

SHEET NO.

I:\MIA\PRJ\000021994\700_CADD\Lighting\Dressels Dairy Trail\GNNTLT01.dwg

Hernandez, Kevin

4/8/2025 1:12:51 F

CITY OF DORAL
Public Works Department

Permit #PWUT-2505-0061

SPECIAL NOTES

- 1. THE ELECTRICAL CONTRACTOR SHALL VERIFY ALL UTILITIES BY ELECTRONIC METHODS AND PRE-TRENCHING IN COORDINATION WITH ALL UTILITY COMPANIES, PRIOR TO BEGINNING ANY CONSTRUCTION OPERATIONS.
- 2. THE CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT ALL EXISTING UNDERGROUND AND ABOVE GROUND IMPROVEMENTS SUCH AS CONDUITS, GAS MAINS, SANITARY SEWER LINES, TV CABLE, TELEPHONE, LATERALS, WATER MAINS, POLES, PIPES, CABLES AND OTHER STRUCTURES FROM INJURY, AND IN CASE OF DAMAGE THEY SHALL BE RESTORED WITHOUT COMPENSATION.
- 3. HAND-DIG WHERE THERE IS ANY CONFLICT WITH THE EXISTING UNDERGROUND UTILITIES.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTACT ALL UTILITY COMPANIES FOR LOCATION OF THEIR EXISTING FACILITIES. IT'S THE CONTRACTOR'S RESPONSIBILITY TO LOCATE THESE UTILITIES FOR THE EXACT DEPTH. CONTACT "SUNSHINE"AT 811 PRIOR TO DIGGING.
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL DAMAGES SUSTAINED OR COST INCURRED BECAUSE OF THE CONTRACTOR'S OPERATION IN THE VICINITY OF EXISTING UTILITIES OR STRUCTURES. THE CONTRACTOR SHALL NOTIFY THE APPROPRIATE UTILITY COMPANIES WHEN THEIR EXISTING FACILITIES CONFLICT WITH THE CONSTRUCTION.
- 6. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE TO CONTACT/LOCATE OTHER UTILITIES NOT SUBSCRIBING TO "SUNSHINE".
- 7. CONTRACTOR TO USE CAUTION WHEN WORKING UNDER AND IN THE VICINITY OF OVERHEAD AND UNDERGROUND UTILITIES. PROVIDE A LETTER FROM FPL APPROVING METHOD OF LIGHT POLE INSTALLATION. CONTACT JESSICA SALAZAR AT JESSICA.SALAZAR@FPL.COM PRIOR TO CONSTRUCTION.
- 8. LIGHT POLE USED AS BASIS OF DESIGN IS HAPCO'S ROUND TAPERED ALUMINUM (RTA) POLE, OR APPROVED EQUAL. POLES SHALL BE DIRECT BURIED AS PER MANUFACTURER'S RECOMMENDATION AND DESIGNED FOR A WIND SPEED ACCORDING TO THE 2020 FLORIDA BUILDING CODE.
- 9. CONTRACTOR IS TO REMOVE ALL SHRUBS/BUSHES WITHIN A 4 FT RADIUS OF ALL LIGHT POLE LOCATIONS TO ALLOW ADEQUATE SPACE FOR ACCESS AND MAINTENANCE. TRIM TREE BRANCHES WITHIN 2 FT RADIUS OF ALL LIGHT POLE LOCATIONS. VERIFY OWNERSHIP AND COORDINATE REMOVAL AND TRIMMING OF BUSHES, SHRUBS, AND TREES WITH OWNER. REPLACE ANY REMOVED TREES, BUSHES, AND SHRUBS IN KIND.

GUARANTEE

THE CONTRACTOR SHALL SUBMIT A WRITTEN GUARANTEE COVERING ALL MATERIALS, WORKMANSHIP, AND EQUIPMENT FOR A PERIOD OF ONE (1) YEAR COMMENCING FROM THE DAY OF FINAL ACCEPTANCE. ANY REPAIRS DUE TO DEFECTIVE WORKMANSHIP OR MATERIALS DURING THE ONE-YEAR PERIOD SHALL BE MADE BY THE CONTRACTOR WITHOUT CHARGE TO THE CITY.

DATE DESCRIPTION PLOCHNEI

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



GENERAL NOTES

SHEET NO.


I:\MIA\PRJ\000021994\700_CADD\Lighting\Dressels Dairy Trail\GNNTLT02.dwg


Hernandez, Kevin

4/8/2025 10:03:55

CITY OF DORAL
Public Works Department
Permit #PWUT-2505-0061

RECEIVED: 05/06/2025





	REVISIONS		
DATE	DESCRIPTION		
		3	Lochner

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



TYPICAL SECTIONS

SHEET NO.	

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025

LEGEND

SYMBOLS

DESCRIPTION

Q

POST TOP LIGHT POLE WITH 54W LED LUMINAIRE DESIGNED FOR 5,983 LUMENS, TYPE IV DISTRIBUTION, 4000K CCT, AND WIRED FOR 240V OPERATION. USE LITHONIA'S RADIAN POST TOP LED WITH CURVE RADPT_LED_P3_40K_PATH_HS. LUMINAIRES TO BE EQUIPPED WITH HOUSE SIDE SHIELDS.



POST TOP LIGHT POLE WITH 86W LED LUMINAIRE DESIGNED FOR 9,209 LUMENS, TYPE IV DISTRIBUTION, 4000K CCT, AND WIRED FOR 240V OPERATION. USE LITHONIA'S RADIAN POST TOP LED WITH CURVE RADPT_LED_P4_40K_PATH_HS. LUMINAIRES TO BE EQUIPPED WITH HOUSE SIDE SHIELDS.



EXISTING POLE LIGHT TO REMAIN



EXISTING SOLAR POWERED LIGHT POLE TO BE REMOVED AND DISPOSED.



EXISTING LIGHT POLE AND FOUNDATION TO BE REMOVED AND DISPOSED.



PROPOSED LOAD CENTER



EXISTING LOAD CENTER



2" SCHEDULE 40 PVC CONDUIT, DIRECT BURIED IN OPEN TRENCH, CONTAINING CIRCUIT CONDUCTORS AS INDICATED ON PLANS. ALL CONDUCTORS SHALL BE STRANDED COPPER WITH THWN-2 INSULATION. GROUND CONDUCTORS SHALL HAVE GREEN COLOR INSULATION. RUN GROUND CONDUCTORS WITH OTHER CONDUCTORS.



2" HDPE CONDUIT INSTALLED BY DIRECTIONAL BORE, CONTAINING CIRCUIT CONDUCTORS AS INDICATED ON PLANS. ALL CONDUCTORS SHALL BE STRANDED COPPER WITH THWN-2 INSULATION. GROUND CONDUCTORS SHALL HAVE GREEN COLOR INSULATION. RUN GROUND CONDUCTORS WITH OTHER CONDUCTORS.



PULL BOX

1. COORDINATE LIGHT POLE AND LUMINAIRE COLORS WITH THE CITY OF DORAL PRIOR TO PROCUREMENT.

	REVISIONS		
DATE	DESCRIPTION	1	
			Lochner

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 HW INCHNER INC CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING *IMPROVEMENTS*



PEDESTRIAN WAYS AND BICYCLE WAYS

LIGHTING CRITERIA

(DRESSEL'S DAIRY TRAIL)

2.0 FOOT CANDLES

3:1 OR LESS

160 MPH

AVERAGE MAINTAINED INTENSITY

UNIFORMITY RATIO AVG./MIN.

UNIFORMITY RATIO MAX./MIN.

WIND SPEED

LE GEND

I:\MIA\PRJ\000021994\700_CADD\Lighting\Dressels Dairy Trail\GNNTLT03.dwg

SHEET

Hernandez, Kevin

Lighting Data Table

	Lighting Data Table						Pei	rmit #PWUT-2505-0														
Pole No.	Easting	Northing	Baseline	Station	Offset	Foundation	Arm Length	Arm Rise	Mount Height	Quantity Luminaires	Туре	Make∖ Model	Lumens	IES Dist Type	CCT(K)	Tilt (deg)	Luminaire Watts	Luminaire Volts	Load Center No.	Circuit No.		CEIVED: 05/06/20
P-1	858256.4528	542886.4028	NW 58TH ST	11+10.36	72.13' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	С	2	Doral	715-516-110
P-2	858308.2310	542892.2170	NW 58TH ST	11+62.18	66.71' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	С	2	Doral	715-516-110
P-3	858358.6850	542902.3290	NW 58TH ST	12+12.71	56.98' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	С	2	Doral	715-516-110
P-4	858410.2530	542910.8110	NW 58TH ST	12+64.34	48.88' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	С	2	Doral	715-516-110
P-5	858462.6340	542912.2557	NW 58TH ST	13+16.73	47.83' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-6	858514.6324	542912.6481	NW 58TH ST	13+68.73	47.83' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-7	858566.6306	542912.6192	NW 58TH ST	14+20.72	48.25' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-8	858618.6300	542912.6978	NW 58TH ST	14+72.72	48.56' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-9	858670.6258	542913.3610	NW 58TH ST	15+24.72	48.29' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-10	858722.6216	542914.0242	NW 58TH ST	15+76.72	48.02' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-11	858774.6179	542914.6348	NW 58TH ST	16+28.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-12	858826.6164	542915.0243	NW 58TH ST	16+80.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-13	858878.6150	542915.4138	NW 58TH ST	17+32.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-14	858930.6119	542915.8041	NW 58TH ST	17+84.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-15	858982.6104	542916.1949	NW 58TH ST	18+36.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-16	859034.6090	542916.5856	NW 58TH ST	18+88.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-17	859086.6075	542916.9764	NW 58TH ST	19+40.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-18	859138.6060	542917.3671	NW 58TH ST	19+92.72	47.80' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-19	859190.6046	542917.7507	NW 58TH ST	20+44.72	47.81' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-20	859242.6032	542918.1387	NW 58TH ST	20+96.72	47.81' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-21	859294.6017	542918.5294	NW 58TH ST	21+48.72	47.81' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	5983	IV	4000K	0	54	240V	С	2	Doral	715-516-110
P-22	859347.0700	542913.2790	NW 58TH ST	21+01.15	53.45' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	С	2	Doral	715-516-110
P-23	859404.7410	542914.1490	NW 58TH ST	22+58.82	53.02' RT	DIRECT	N/A	N/A	10'	1	POST TOP	RADPT	9209	IV	4000K	0	86	240V	С	2	Doral	715-516-110

DATE DESCRIPTION

P Lochner

JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



POLE DATA

SHEET NO.

L-7


Hernandez, Kevin

4/8/2025 10:04:21 A

I:\MIA\PRJ\000021994\700_CADD\Lighting\Dressels Dairy Trail\PLDTLT01.dwg

CITY OF DORAL
Public Works Department

Public Works Department Permit #PWUT-2505-0061 RECEIVED: 05/06/2025



	REVISIONS
DATE	DESCRIPTION
	1

4 Lochner


JOSEPH M. CALDERON TORRES II, P.E.
P.E. LICENSE NUMBER 90625
H.W. LOCHNER, INC.
CONSULTING ENGINEERS AND PLANNERS
8750 NW 36th STREET - SUITE 360
MIAMI, FLORIDA - 33178


CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS





PROJECT LAYOUT


SHEET NO. L-8




















BOND LIGHT POLE METAL TO GROUND -CONDUCTORS, FOR SPLICE (GELCAP) -SIZE AND QUANTITY SEE EXOTHERMIC — PLANS CONNECTION 13" X 24" X 12" -PULL BOX 12" BED OF -PEAROCK OR CRUSHED STONE FOR DRAINAGE STRAIN RELIEF FITTINGS 5" DIA. X 20' LONG GROUND ROD PULL BOX DETAIL

LIGHT POLE DETAIL

	REVISIONS	
DATE	DESCRIPTION	
		Lochner

JOSEPH M. CALDERON TORRES II, P.E. P.E. LICENSE NUMBER 90625 H.W. LOCHNER, INC. CONSULTING ENGINEERS AND PLANNERS 8750 NW 36th STREET - SUITE 360 MIAMI, FLORIDA - 33178

CITY OF DORAL TRAIL LIGHTING IMPROVEMENTS



LIGHT POLE DETAIL

	VO.
L-	-16